

INDUSTRIAL COMPONENT DATA

isFang 3B-150 5408969 OBO BETTERMANN Tripod stand for insulated interception rod, 1,65x1,85m, Stainless steel..

Brand: OBO BETTERMANN | Manufacturer Part Number: isFang 3B-150



Manufacturer	OBO BETTERMANN
MPN / Reference	isFang 3B-150
Catalog number	5408969
Category	Base for air termination systems lightning protection
Minimum order	1 Pcs
Document ID	EO-BDFDB63ECB
Generated	2026-08-02

Product Overview

Tripod stand for insulated interception rod, 1,65x1,85m, Stainless steel, grade 304, VA, 1.4301
isFang 3B-150 tripod stand, for collector tips 1.65x1.85m Stainless steel 1.4301, A2, 1.4301,

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external

Additional Product Information

Folding tripod stand for screwless installation of free-standing interception rods with a diameter of 40 mm, and.g. for OBO isCon® cable. Roof slope to max. 5 degrees. Incl. Rd 8-10 crossbar for rapid round conductor fastening. The concrete plinth and threaded rods are to be ordered separately.

ETIM for 5408969 Earthing, lightning and surge protection (EC001626)

Feature Name

Feature Value

Model (EF000010)

Tripod

Lightning conductor insertion (EF004180)

Screwless

Material (EF002169)

Stainless steel 304

Diameter (EF000551)

1500 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / isFang 3B-150 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.