

INDUSTRIAL COMPONENT DATA

isFang 3B-150 AL 5408967 OBO BETTERMANN Tripod stand for insulated interception rod, 1,65x1,85m, Aluminium, ..

Brand: OBO BETTERMANN | Manufacturer Part Number: isFang 3B-150 AL



Manufacturer	OBO BETTERMANN
MPN / Reference	isFang 3B-150 AL
Catalog number	5408967
Category	Base for air termination systems lightning protection
Minimum order	1 Pcs
Document ID	EO-A211E75C6D
Generated	2026-08-01

Product Overview

Tripod stand for insulated interception rod, 1,65x1,85m, Aluminium, Alu isFang tripod. • Installation of free-standing air-termination rods as well as insulated air-termination rods with 40 mm diameter • Roof slope to max. 5 degrees • Incl. Rd 8-10 crossbar for quick round conductor fastening • Concrete base as well as threaded rods should be ordered separately

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external

Additional Product Information

Air-termination rod holder Screwless
CO2 Footprint (GWP) Cradle-to-Gate 27,3315 kg CO2e / 1 Piece
Diameter 1500 mm
Dimension 1,65x1,85m
Dimension B 1500 mm
Dimension d min. 40 mm
Dimension H 1275 mm
Dimension L 900 mm
Height 1275 mm
Length 900 mm
Material Aluminium
Version for Stand

Width 1500 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / isFang 3B-150 AL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.