

INDUSTRIAL COMPONENT DATA

RD 10-PVC 5021162 OBO BETTERMANN Round conductors with PVC sheathing, 10mm, Black, Hot-dip galvanised, DIN E..

Brand: OBO BETTERMANN | Manufacturer Part Number: RD 10-PVC



Manufacturer	OBO BETTERMANN
MPN / Reference	RD 10-PVC
Catalog number	5021162
Category	Round conductor/wire for lightning protection
Minimum order	75 Pcs
Document ID	EO-914FE3D5B0
Generated	2026-08-02

Product Overview

Round conductors with PVC sheathing, 10mm, Black, Hot-dip galvanised, DIN EN ISO 1461, Steel, St
Round conductor, galvanised steel with PVC jacketing. • Can be used as an earthing conductor• Corresponds to the requirements of VDE 0185-305 (IEC 62305)• Zinc coating: $\geq 350 \text{ g/m}^2$ (approx. $50 \mu\text{m}$ in mean value)• With PVC jacketing

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external**

Additional Product Information

Colour Black
Cross-section 78 mm^2
Diameter 10 mm
Dimension 10mm
Dimension D 13 mm
Dimension d 10 mm
High voltage-resistant, insulated version no
Length tolerance $\pm 5 \%$
Material Steel
Material jacket PVC
Material property Miscellaneous
Nomal ring (approx. m) 75
Normal ring (ca. kg) 50

Number of individual wires 1

Surface Hot-dip galvanised

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / RD 10-PVC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.