

INDUSTRIAL COMPONENT DATA

V25-B+C 3-PH900 5097447 OBO BETTERMANN

CombiController V25 three-pole for photovoltaics, 900V,

Brand: OBO BETTERMANN | Manufacturer Part Number: V25-B+C 3-PH900



Manufacturer	OBO BETTERMANN
MPN / Reference	V25-B+C 3-PH900
Catalog number	5097447
Category	Combined arrester for power supply systems
Minimum order	1 Pcs
Document ID	EO-2F8ACC0AE7
Generated	2026-08-02

Product Overview

CombiController V25 three-pole for photovoltaics, 900V,
PV combination arrester V25, 900 V DC. V25 combination arrester, type 1+2, for photovoltaic systems• Complete unit, consisting of plug-in varistor arrester with cut-off unit• Error-resistant Y circuit to VDE 0100-712 (EN 50539-12)• Surge protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)• Arresting capacity up to 7 kA (10/350) and 50 kA (8/20) per pole• Low DC protection level: < 3.0 kV and Voc max = 900 V DC• With visual function display for use in distributor housings Application: PV systems with lightning protection system

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , photovol
--------------	---

Additional Product Information

Blow-out no
CO2 Footprint (GWP) Cradle-to-Gate 0,9501 kg CO2e / 1 Piece
Conductor cross-section, rigid (single-wire/multiwire), max. 35 mm²
Conductor cross-section, rigid (single-wire/multiwire), min. 2,5 mm²
DC network form yes
Dimension 900V DC
Installation type DIN rail 35 mm
IT network form no
Lightning protection zone LPZ 0->2
Lightning surge current (10/350 us) 7 kA

Max. mains-side overcurrent protection 160
Maximum back-up fuse 160 A
Maximum continuous voltage DC 900 V
Maximum discharge current (8/20 us) 50 kA
Network form DC
Nominal discharge current (8/20 µs) 30 kA
Nominal discharge current (8/20 µs) [L-N] 30 kA
Operating temperature, max. 80 °C
Operating temperature, min. -40 °C
Other network form no
Permitted temperature range, max. 80 °C
Permitted temperature range, min. -40 °C
Pole version 3
Protection rating IP20
Remote signalling no
Response time

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / V25-B+C 3-PH900 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.