

INDUSTRIAL COMPONENT DATA

450 M4x95 G 3481611 OBO BETTERMANN Sprung hinged anchor , M4x95mm, Electrogalvanised, DIN 50961, Steel, St

Brand: OBO BETTERMANN | Manufacturer Part Number: 450 M4x95 G



Manufacturer	OBO BETTERMANN
MPN / Reference	450 M4x95 G
Catalog number	3481611
Category	Toggle fixing
Minimum order	50 Pcs
Document ID	EO-F464E1F4DD
Generated	2026-07-31

Product Overview

Sprung hinged anchor , M4x95mm, Electrogalvanised, DIN 50961, Steel, St
Sprung hinged anchor. With threaded rod, washer and hexagonal nut, steel axle.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > Tilting**

Additional Product Information

Breaking load 0,2 kN
Dimension M4x95mm
Drill hole 14 mm
Drill hole diameter, min. 14 mm
Length 90 mm
Material Steel
Minimum cavity depth 35 mm
Surface Electrogalvanized
Thread M4
Thread type Metric
Version for With threaded shaft
With washer yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 450 M4x95 G with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.