

INDUSTRIAL COMPONENT DATA

451 M4x95 G 3481662 OBO BETTERMANN Sprung hinged anchor , M4x95mm, Electrogalvanised, DIN 50961, Steel, St

Brand: OBO BETTERMANN | Manufacturer Part Number: 451 M4x95 G



Manufacturer	OBO BETTERMANN
MPN / Reference	451 M4x95 G
Catalog number	3481662
Category	Toggle fixing
Minimum order	50 Pcs
Document ID	EO-71E4A3A104
Generated	2026-08-02

Product Overview

Sprung hinged anchor , M4x95mm, Electrogalvanised, DIN 50961, Steel, St

Sprung hinged anchor. With threaded rod and slotted brass nut, steel axle.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > Tilting

Additional Product Information

Breaking load 0,2 kN

Dimension M4x95mm

Drill hole 14 mm

Drill hole diameter, min. 14 mm

Length 90 mm

Material Steel

Minimum cavity depth 35 mm

Surface Electrogalvanized

Thread M4

Thread type Metric

Version for With threaded shaft

With washer no

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 451 M4x95 G with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.