

INDUSTRIAL COMPONENT DATA

UDSSD 25038 4 7400349 OBO BETTERMANN BOX FOR CONJ.PORTAMEC. UDSSD 25038 4

Brand: OBO BETTERMANN | Manufacturer Part Number: UDSSD 25038 4



Manufacturer	OBO BETTERMANN
MPN / Reference	UDSSD 25038 4
Catalog number	7400349
Category	Service box for underfloor installation
Minimum order	1 Pcs
Document ID	EO-D815D2B2FB
Generated	2026-08-04

Product Overview

BOX FOR CONJ.PORTAMEC. UDSSD 25038 4

Box for Conjuntoportamecanismos, for GES4, 308x308x92, galvanized steel in band, DIN EN 10346

Underfloor box UDS4 for installation pipe and metal duct. Underfloor outlet box with fixed, unchangeable 201 x 201 mm installation opening for an installation unit of nominal size 4. The mounting opening is created using the screed protection cover contained in the scope of supply. The underfloor box possesses installation openings for a 2 or 3-compartment sheet steel underfloor duct of nominal size 25038 as well as six M20 or M25 installation pipes on all four sides. The box is principally suited for use in floor structures in cement screed with a structure height of up to 90 mm.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > UFS Underfloor piping systems - OBO BETTERMANN

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 9,8986 kg CO2e / 1 Piece

Decouplable no

Dimension 308x308x92

Duct height, min. 38 mm

Floor plate no

For pipe connection yes

Height 92 mm

Height-adjustment range, max. 95 mm

Height-adjustment range, min. 62 mm

Installation opening for flush-mount unit Square
Installation opening for on-floor tank no
Length 308 mm
Lowerable to be flush-floor no
Material Steel
Nominal size 308 mm
Nominal size for device installation units 4
Number of installable devices 1
Protection rating (IP) when used IP20
Screed height, max. 90 mm
Screed height, min. 65 mm
Seal installation option yes
Suitable for screed-covered underfloor ducts yes
Suitable for screed-flush closed underfloor ducts no
Suitable for underfloor ducts no
Surface Strip galvanized
Trunking height, max. 38 mm
Trunking width, max. 250 mm
Trunking width, min. 250 mm
Width 308 mm
ETIM for 7400349 Underfloor trunking and floor boxes (EC000893)
Feature Name
Feature Value
Nominal dimension (EF000132)
308 mm
Min. height finishing layer (EF007935)
65 mm
Levelling range (EF005136)
62 mm
Suitable for subfloor duct countersunk (closed) (EF005792)
Yes
Suitable for subfloor duct overhead closed (EF006408)
No
Duct height (EF005459)
38 mm
Duct width (EF007884)
250 mm
Built-in opening for floor column (EF004641)
No
Built-in opening for built-in unit (EF007738)
Square
Number of appliances to build in (EF000219)
1
Material side wall (EF008133)
Steel
Suitable for placing of sealing (EF004594)
Yes

Decoupling possibi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / UDSSD 25038 4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.