


INDUSTRIAL COMPONENT DATA

GES6M-2 10U 7405299 OBO BETTERMANN Service outlet for universal mounting, Stainless steel, grade 304, VA, 1...

Brand: OBO BETTERMANN | Manufacturer Part Number: GES6M-2 10U



Manufacturer	OBO BETTERMANN
MPN / Reference	GES6M-2 10U
Catalog number	7405299
Category	Installation box for underfloor-installation
Minimum order	1 Pcs
Document ID	EO-1136231DC6
Generated	2026-07-29

Product Overview

Service outlet for universal mounting, Stainless steel, grade 304, VA, 1.4301
GES6M-2 service outlet with handle clamp. Service outlet with handle clamp for up to 9 individual Modul 45 devices in 3 UT3 universal supports, use in trunking systems and system floors for indoor use. Locking ladder made of galvanised sheet steel. The floor covering thickness is set to 5 mm, adjustable to 10 mm if necessary. Service outlet with handle clamp, 3-compartment, for the installation of MT6 mounting support. Three type APMT2 cover plates can be installed.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > UFS Underfloor piping systems - OBO BETTERMANN > Other

Additional Product Information

Cable outlet version Swivellable cord outlet
Clamping range D, max. 61 mm
Clamping range D, min. 3 mm
CO2 Footprint (GWP) Cradle-to-Gate 18,9807 kg CO2e / 1 Piece
Device support to accept mounting boxes yes
Dimension 274x221x70
Floor care Dry
Floor covering protection frame yes
Floor covering thickness 5 mm
Floor covering thickness max. 10 mm
Floor height, min. 78 mm

Frame version Carpet protection frame
Heavy-duty version no
Installation depth 78 mm
Installation system type MT3 / GB2
Length 274 mm
Length of external dimensions 274 mm
Length of installation dimensions 253 mm
Material Stainless steel 1.4301
Nominal size for device installation units 6
Number of installable devices 9
Number of mounting boxes 3
Opening mechanism Handle
Protection rating (IP) when unused IP40
Protection rating (IP) when used IP20
Protection rating IK code IK10
Seal installation option no
Suitable for cavity floor installation yes
Suitable for raised floor installation yes
Suitable for screed-covered underfloor ducts yes
Suitable for screed-flush closed underfloor ducts no
Suitable for underfloor ducts yes
Suitable for wet care no
Version for Rectangular
Vertical load, large area to 5,000 N
Vertical load, small area to 3,000 N
Wide external dimensions 220,5 mm
Wide installation dimensions 200 mm
Width 220,5 mm
With floor covering recess yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / GES6M-2 10U with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.