

**INDUSTRIAL COMPONENT DATA**

# GES9 55U V 9011 7405039 OBO BETTERMANN Service outlet for duct mounting, Graphite black, 9011, Polyamide, PA

Brand: OBO BETTERMANN | Manufacturer Part Number: GES9 55U V 9011



|                 |                                              |
|-----------------|----------------------------------------------|
| Manufacturer    | OBO BETTERMANN                               |
| MPN / Reference | GES9 55U V 9011                              |
| Catalog number  | 7405039                                      |
| Category        | Installation box for underfloor-installation |
| Minimum order   | 1 Pcs                                        |
| Document ID     | EO-3199F99BF3                                |
| Generated       | 2026-08-01                                   |

## Product Overview

Service outlet for duct mounting, Graphite black, 9011, Polyamide, PA

Service outlet, square, for screed height 55 mm. GES9 service outlet with a fixed construction height of 55 mm for use in installation trunking systems in dry rooms with dry-care floors in interior areas. With two installation housings for vertical mounting of Modul 45 devices and four strain reliefs. Two installation frames are required to mount Modul 45 devices. The data modules are mounted using a maximum of two optional MPMT45 mounting plates. The service outlet is equipped with universal fastening brackets.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      OBO BETTERMANN &gt; UFS Underfloor piping systems - OBO BETTERMANN &gt; Other

## Additional Product Information

Cable outlet version Swivellable cord outlet  
 Clamping range D, max. 31 mm  
 Clamping range D, min. 9 mm  
 CO2 Footprint (GWP) Cradle-to-Gate 6,3663 kg CO2e / 1 Piece  
 Colour Graphite black; RAL 9011  
 Device support to accept mounting boxes no  
 Dimension 263x263x59  
 Dimension h 55 mm  
 Floor care Dry  
 Floor covering protection frame yes

Floor covering thickness 5 mm  
Floor height, min. 58 mm  
Frame version Carpet protection frame  
Heavy-duty version no  
Height 59 mm  
Installation depth 58 mm  
Length 263 mm  
Length of external dimensions 263 mm  
Length of installation dimensions 242 mm  
Material Polyamide  
Nominal size for device installation units 9  
Number of installable devices 8  
Opening mechanism Handle  
Screed height, min. 55 mm  
Seal installation option no  
Suitable for cavity floor installation yes  
Suitable for raised floor installation yes  
Suitable for screed-covered underfloor ducts yes  
Suitable for screed-flush closed underfloor ducts yes  
Suitable for underfloor ducts yes  
Suitable for wet care no  
Version for Square  
Vertical load, large area to 5,000 N  
Vertical load, small area to 3,000 N  
Wide external dimensions 263 mm  
Wide installation dimensions 242 mm  
Width 263 mm  
With floor covering recess no

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / GES9 55U V 9011 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.