

INDUSTRIAL COMPONENT DATA

GESR9 55U V 9011 7405049 OBO BETTERMANN Service outlet for duct mounting, Graphite black, 9011, Polyamide, PA

Brand: OBO BETTERMANN | Manufacturer Part Number: GESR9 55U V 9011



Manufacturer	OBO BETTERMANN
MPN / Reference	GESR9 55U V 9011
Catalog number	7405049
Category	Installation box for underfloor-installation
Minimum order	1 Pcs
Document ID	EO-66F1470C22
Generated	2026-08-03

Product Overview

Service outlet for duct mounting, Graphite black, 9011, Polyamide, PA

Service outlet, round, for screed height 55 mm. GESR9 service outlet with a fixed construction height of 55 mm for indoor use. With two fitted plug housings for vertical mounting of Modul 45 devices and four strain reliefs. Two installation frames are required to mount Modul 45 devices. The data modules are mounted using an optional mounting plate MPMT45. The service outlet is equipped with universal fastening brackets.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > UFS Underfloor piping systems - OBO BETTERMANN > Other

Additional Product Information

Cable outlet version Swivellable cord outlet
 Clamping range D, max. 28 mm
 Clamping range D, min. 10 mm
 CO2 Footprint (GWP) Cradle-to-Gate 7,7792 kg CO2e / 1 Piece
 Colour Graphite black; RAL 9011
 Device support to accept mounting boxes no
 Dimension Ø325x61
 External diameter 325 mm
 Floor care Dry
 Floor covering protection frame yes
 Floor covering thickness 5 mm

Floor height, min. 58 mm
Heavy-duty version no
Height 61 mm
Installation depth 58 mm
Installation diameter 304
Length 325 mm
Material Polyamide
Nominal size for device installation units R9
Number of installable devices 8
Opening mechanism Handle
Screed height, min. 55 mm
Seal installation option no
Suitable for cavity floor installation yes
Suitable for raised floor installation yes
Suitable for screed-covered underfloor ducts yes
Suitable for screed-flush closed underfloor ducts yes
Suitable for underfloor ducts yes
Suitable for wet care no
Version for Round
Vertical load, large area to 5,000 N
Vertical load, small area to 3,000 N
Width 325 mm
With floor covering recess no

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / GESR9 55U V 9011 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.