

**INDUSTRIAL COMPONENT DATA**

# OKA-G40040150FBR 7423974 OBO BETTERMANN Branch, right for OKA-G and OKA-W, Strip-galvanised, DIN EN 10147, S..

Brand: OBO BETTERMANN | Manufacturer Part Number: OKA-G40040150FBR



|                 |                                                                 |
|-----------------|-----------------------------------------------------------------|
| Manufacturer    | OBO BETTERMANN                                                  |
| MPN / Reference | OKA-G40040150FBR                                                |
| Catalog number  | 7423974                                                         |
| Category        | Junction unit for underfloor installation duct flush floor open |
| Minimum order   | 1 Pcs                                                           |
| Document ID     | EO-3C5942145F                                                   |
| Generated       | 2026-08-03                                                      |

## Product Overview

Branch, right for OKA-G and OKA-W, Strip-galvanised, DIN EN 10147, Steel, St  
Construction set for 90° angle to right, height 40–150 mm. For the construction-side creation of a trunking junction as a 90° angle, T-piece or crossing. A flushfloor end cover is also required for the creation of a 90° angle (order separately). Suitable for the OKA-G and OKA-W trunking systems.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      OBO BETTERMANN &gt; UFS Underfloor piping systems - OBO BETTERMANN &gt; Other

## Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 7,3582 kg CO2e / 1 Piece  
Cover fastening, locking no  
Decouplable no  
Duct height, min. 40 mm  
Floor plate no  
Function Branch  
Height-adjustment range, max. 110 mm  
Installation opening for on-floor tank no  
Length 460 mm  
Material Steel

Minimum screed height 40  
Mounting opening cover no  
Removable cover no  
Seal installation option no  
Suitable for expansion joint no  
Suitable for flushfloor, open underfloor trunking no  
Suitable for screed-covered underfloor ducts no  
Suitable for screed-flush closed underfloor ducts no  
Surface Strip galvanized  
Trunking height, max. 150 mm  
Width 400 mm  
With connection opening no  
With equipotential bonding no  
With overhang yes  
With separating retainer no

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / OKA-G40040150FBR with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.