


INDUSTRIAL COMPONENT DATA

OKA-W A 10050R9 7424926 OBO BETTERMANN Extension unit for OKA-W, Strip-galvanised, DIN EN 10147, Steel, St

Brand: OBO BETTERMANN | Manufacturer Part Number: OKA-W A 10050R9



Manufacturer	OBO BETTERMANN
MPN / Reference	OKA-W A 10050R9
Catalog number	7424926
Category	Underfloor installation duct flush floor open
Minimum order	1 Pcs
Document ID	EO-7208002DA2
Generated	2026-08-03

Product Overview

Extension unit for OKA-W, Strip-galvanised, DIN EN 10147, Steel, St

Extension unit for GESR9, height 100–150 mm. Ready-to-mount trunking extension unit with a device installation lid for the installation of a flush-mount unit of nominal size R9, consisting of the trunking base (floor trough with side and floor covering contact profiles), trunking lid with blank mounting opening and a flushfloor end cover. The scope of delivery contains 3 height-adjustable fixing brackets, 3 screed anchors, 1 lid butt support and 1 construction set for 90° angle.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > UFS Underfloor piping systems - OBO BETTERMANN > Other

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 50,8516 kg CO2e / 1 Piece

Cover fastening, locking no

Cover material thickness 4

Covers 1

Decouplable no

Dimension A 400 mm

Dimension d Ø 305 mm

Dimension h 100 mm

Duct height, min. 100 mm

Height-adjustment range, max. 150 mm

Height-adjustment range, min. 100 mm

Installation opening for flush-mount unit Round
Installation opening for on-floor tank no
Length 473 mm
Material Steel
Minimum screed height 100
Mounting opening For service outlet
Mounting opening cover yes
Nominal size for device installation units R9
Number of mounting openings 1
Removable cover yes
Seal installation option yes
Suitable for expansion joint no
Suitable for flushfloor, open underfloor trunking yes
Suitable for screed-covered underfloor ducts no
Suitable for screed-flush closed underfloor ducts no
Surface Strip galvanized
Trunking height, max. 150 mm
Width 400 mm
With connection opening yes
With equipotential bonding no
With overhang yes
With separating retainer no

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / OKA-W A 10050R9 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.