

INDUSTRIAL COMPONENT DATA

OKA-W20010050 7424440 OBO BETTERMANN Flushfloor trunking unit blank, 2400x200x100, Strip-galvanised, DIN EN ..

Brand: OBO BETTERMANN | Manufacturer Part Number: OKA-W20010050



Manufacturer	OBO BETTERMANN
MPN / Reference	OKA-W20010050
Catalog number	7424440
Category	Underfloor installation duct flush floor open
Minimum order	2 Pcs
Document ID	EO-8E17E1E3FC
Generated	2026-08-01

Product Overview

Flushfloor trunking unit blank, 2400x200x100, Strip-galvanised, DIN EN 10147, Steel, St
OKA-W20010050 flush pavement channel, blind 2400x200x100 Steel, St, strip galvanized, DIN EN 10346
Trunking unit, blank, height 100–150 mm. Ready-to-mount trunking unit with three blanking lids for cable laying, consisting of the trunking base (floor trough with side and floor covering contact profiles) and trunking lid. Floor trough with holding straps for self-contacting mounting of separating retainers. The scope of delivery contains 6 height-adjustable fixing brackets, 6 screed anchors and lid butt seals (3x for nominal trunking widths of 200 and 300) or height-adjustable lid butt supports: 3x for nominal trunking width 400 and 6x for nominal trunking widths 500 and 600. Trunking lid screwed on for delivery.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > UFS Underfloor piping systems - OBO BETTERMANN > Other
--------------	---

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 51,9426 kg CO2e / 1 Meter
Cover fastening, locking no
Cover material thickness 4
Covers 3
Decouplable no
Dimension 2400x200x100
Duct height, min. 100 mm
Floor plate yes

Height-adjustment range, max. 150 mm
Height-adjustment range, min. 100 mm
Installation opening for on-floor tank no
Length 2400 mm
Material Steel
Minimum screed height 100
Mounting opening Without
Mounting opening cover no
Number of compartments 2 St.
Number of insertable partitions 1
Number of planned flush-mount units 3
Removable cover yes
Seal installation option yes
Separating retainer fastening Lock
Suitable for expansion joint no
Surface Strip galvanized
Trunking height, max. 150 mm
Usable cross-section 10200 mm²
Width 200 mm
With connection opening no
With equipotential bonding no
With overhang yes
With separating retainer no

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / OKA-W20010050 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.