


INDUSTRIAL COMPONENT DATA

OKA-W40010050D4 7424622 OBO BETTERMANN Flushfloor trunking unit for service unit GES19, 2400x400x100, Strip-..

Brand: OBO BETTERMANN | Manufacturer Part Number: OKA-W40010050D4



Manufacturer	OBO BETTERMANN
MPN / Reference	OKA-W40010050D4
Catalog number	7424622
Category	Underfloor installation duct flush floor open
Minimum order	2 Pcs
Document ID	EO-CE09E07848
Generated	2026-08-01

Product Overview

Flushfloor trunking unit for service unit GES19, 2400x400x100, Strip-galvanised, DIN EN 10147, Steel, St OKA-W40010050D4 pavement flush channel, for conj. portam. GES4 2400x400x100 Steel, St, strip galvanized, DIN EN 10346

Trunking unit for GES4, height 100–150 mm. Ready-to-mount trunking unit with three or six device installation lids for cable laying and the installation of flush-mount units of nominal size 4, consisting of the trunking base (floor trough with side and floor covering contact profiles) and trunking lid with blank covered mounting opening. Floor trough with holding straps for self-contacting mounting of separating retainers. The scope of delivery contains 6 height-adjustable fixing brackets, 6 screed anchors and lid butt seals (3x for nominal trunking widths of 200 and 300) or height-adjustable lid butt supports: 3x for nominal trunking width 400 and 6x for nominal trunking widths 500 and 600. Trunking lid screwed down when delivered.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > UFS Underfloor piping systems - OBO BETTERMANN > Other
--------------	---

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 79,1946 kg CO2e / 1 Meter

Cover fastening, locking no

Cover material thickness 4

Covers 3

Decouplable no

Dimension 2400x400x100

Duct height, min. 100 mm

Floor plate yes
Height-adjustment range, max. 150 mm
Height-adjustment range, min. 100 mm
Installation opening for on-floor tank no
Length 2400 mm
Material Steel
Minimum screed height 100
Mounting opening For service outlet
Mounting opening Square
Mounting opening cover yes
Nominal size for device installation units 4
Number of compartments 3 St.
Number of insertable partitions 2
Number of planned flush-mount units 3
Removable cover yes
Seal installation option yes
Separating retainer fastening Plug
Suitable for expansion joint no
Surface Strip galvanized
Trunking height, max. 150 mm
Width 400 mm
With connection opening yes
With equipotential bonding no
With overhang yes
With separating retainer no

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / OKA-W40010050D4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.