

INDUSTRIAL COMPONENT DATA

OKA-W4006050 7424424 OBO BETTERMANN Flushfloor trunking unit blank, 2400x400x60, Strip-galvanised, DIN EN 10..

Brand: OBO BETTERMANN | Manufacturer Part Number: OKA-W4006050



Manufacturer	OBO BETTERMANN
MPN / Reference	OKA-W4006050
Catalog number	7424424
Category	Underfloor installation duct flush floor open
Minimum order	2 Pcs
Document ID	EO-956B833ABD
Generated	2026-08-03

Product Overview

Flushfloor trunking unit blank, 2400x400x60, Strip-galvanised, DIN EN 10147, Steel, St

OKA-W4006050 flush pavement channel, blind 2400x400x60 Steel, St, strip galvanized, DIN EN 10346

Trunking unit, blank, height 60–110 mm. Ready-to-mount trunking unit with three blanking lids for cable laying, consisting of the trunking base (floor trough with side and floor covering contact profiles) and trunking lid. Floor trough with holding straps for self-contacting mounting of separating retainers. The scope of delivery contains 6 height-adjustable fixing brackets, 6 screed anchors and lid butt seals (3x for nominal trunking widths of 200 and 300) or height-adjustable lid butt supports: 3x for nominal trunking width 400 and 6x for nominal trunking widths 500 and 600. Trunking lid screwed on for delivery.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > UFS Underfloor piping systems - OBO BETTERMANN > Other

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 66,7229 kg CO2e / 1 Meter

Cover fastening, locking no

Cover material thickness 4

Covers 3

Decouplable no

Dimension 2400x400x60

Duct height, min. 60 mm

Floor plate yes
Height-adjustment range, max. 110 mm
Height-adjustment range, min. 60 mm
Installation opening for on-floor tank no
Length 2400 mm
Material Steel
Minimum screed height 60
Mounting opening Without
Mounting opening cover no
Number of compartments 3 St.
Number of insertable partitions 2
Number of planned flush-mount units 3
Removable cover yes
Seal installation option yes
Separating retainer fastening Lock
Suitable for expansion joint no
Surface Strip galvanized
Trunking height, max. 110 mm
Usable cross-section 12400 mm²
Width 400 mm
With connection opening no
With equipotential bonding no
With overhang yes
With separating retainer no

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / OKA-W4006050 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.