


INDUSTRIAL COMPONENT DATA

OKA-W4006050D6 7424662 OBO BETTERMANN Flushfloor trunking unit for service unit GES6, 2400x400x60, Strip-gal..

Brand: OBO BETTERMANN | Manufacturer Part Number: OKA-W4006050D6



Manufacturer	OBO BETTERMANN
MPN / Reference	OKA-W4006050D6
Catalog number	7424662
Category	Underfloor installation duct flush floor open
Minimum order	2 Pcs
Document ID	EO-9094FABC1F
Generated	2026-08-01

Product Overview

Flushfloor trunking unit for service unit GES6, 2400x400x60, Strip-galvanised, DIN EN 10147, Steel, St
OKA-W4006050D6 pavement flush channel, for conj. portam. GES6 2400x400x60 Steel, St, strip galvanized, DIN EN 10346

Trunking unit for GES6, height 60–110 mm. Ready-to-mount trunking unit with three or six device installation lids for cable laying and the installation of installation units of nominal size 6, consisting of the trunking base (floor trough with side and floor covering guide profiles) and trunking lid with blank mounting opening. Floor trough with holding shackles for self-contacting mounting of dividers. The scope of supply contains six height-adjustable wall fixing brackets, six screed anchors and three height-adjustable cover joint supports for nominal trunking width 400 or six height-adjustable cover joint supports for nominal trunking widths 500 and 600. Trunking lid screwed down when delivered.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > UFS Underfloor piping systems - OBO BETTERMANN > Other

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 70,6784 kg CO2e / 1 Meter
Cover fastening, locking no
Cover material thickness 4
Covers 3
Decouplable no
Dimension 2400x400x60
Duct height, min. 60 mm

Floor plate yes
Height-adjustment range, max. 110 mm
Height-adjustment range, min. 60 mm
Installation opening for on-floor tank no
Length 2400 mm
Material Steel
Minimum screed height 60
Mounting opening Square
Mounting opening For service outlet
Mounting opening cover yes
Nominal size for device installation units 6
Number of compartments 3 St.
Number of insertable partitions 2
Number of planned flush-mount units 3
Removable cover yes
Seal installation option yes
Separating retainer fastening Plug
Suitable for expansion joint no
Surface Strip galvanized
Trunking height, max. 110 mm
Width 400 mm
With connection opening yes
With equipotential bonding no
With overhang yes
With separating retainer no

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / OKA-W4006050D6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.