

INDUSTRIAL COMPONENT DATA

OKA-W4006050DR9 7424780 OBO BETTERMANN Flushfloor trunking unit for service unit GESR9, 2400x400x60, Strip-g..

Brand: OBO BETTERMANN | Manufacturer Part Number: OKA-W4006050DR9



Manufacturer	OBO BETTERMANN
MPN / Reference	OKA-W4006050DR9
Catalog number	7424780
Category	Underfloor installation duct flush floor open
Minimum order	2 Pcs
Document ID	EO-0F647E6B4B
Generated	2026-07-29

Product Overview

Flushfloor trunking unit for service unit GESR9, 2400x400x60, Strip-galvanised, DIN EN 10147, Steel, St
OKA-W4006050DR9 pavement flush channel, for conj. portam. GESR9 2400x400x60 Steel, St, strip galvanized, DIN EN 10346

Trunking unit for GESR9, height 60–110 mm. Ready-to-mount trunking unit with three or six device installation lids for cable laying and the installation of flush-mount units of nominal size R9, consisting of the trunking base (floor trough with side and floor covering contact profiles) and trunking lid with blank covered mounting opening. Floor trough with holding straps for self-contacting mounting of separating retainers. The scope of delivery contains 6 height-adjustable fixing brackets, 6 screed anchors and height-adjustable lid butt supports: 3x for nominal trunking width 400 and 6x for nominal trunking widths 500 and 600. Trunking lid screwed down when delivered.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > UFS Underfloor piping systems - OBO BETTERMANN > Other
--------------	---

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 74,0458 kg CO2e / 1 Meter

Cover fastening, locking no

Cover material thickness 4

Covers 3

Decouplable no

Dimension 2400x400x60

Duct height, min. 60 mm

Floor plate yes
Height-adjustment range, max. 110 mm
Height-adjustment range, min. 60 mm
Installation opening for on-floor tank no
Length 2400 mm
Material Steel
Minimum screed height 60
Mounting opening Round
Mounting opening For service outlet
Mounting opening cover yes
Number of compartments 3 St.
Number of insertable partitions 2
Number of planned flush-mount units 3
Removable cover yes
Seal installation option yes
Suitable for expansion joint no
Surface Strip galvanized
Trunking height, max. 110 mm
Width 400 mm
With connection opening yes
With equipotential bonding no
With overhang yes
With separating retainer no

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / OKA-W4006050DR9 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.