

**INDUSTRIAL COMPONENT DATA**

# OKA-W6006050 7424428 OBO BETTERMANN Flushfloor trunking unit blank, 2400x600x60, Strip-galvanised, DIN EN 10..

Brand: OBO BETTERMANN | Manufacturer Part Number: OKA-W6006050



|                 |                                               |
|-----------------|-----------------------------------------------|
| Manufacturer    | OBO BETTERMANN                                |
| MPN / Reference | OKA-W6006050                                  |
| Catalog number  | 7424428                                       |
| Category        | Underfloor installation duct flush floor open |
| Minimum order   | 2 Pcs                                         |
| Document ID     | EO-8927875DE2                                 |
| Generated       | 2026-08-03                                    |

## Product Overview

Flushfloor trunking unit blank, 2400x600x60, Strip-galvanised, DIN EN 10147, Steel, St  
OKA-W6006050 flush pavement channel, blind 2400x600x60 Steel, St, galvanized in band, DIN EN 10346  
Trunking unit, blank, height 60–110 mm. Ready-to-mount trunking unit with three blanking lids for cable laying, consisting of the trunking base (floor trough with side and floor covering contact profiles) and trunking lid. Floor trough with holding straps for self-contacting mounting of separating retainers. The scope of delivery contains 6 height-adjustable fixing brackets, 6 screed anchors and lid butt seals (3x for nominal trunking widths of 200 and 300) or height-adjustable lid butt supports: 3x for nominal trunking width 400 and 6x for nominal trunking widths 500 and 600. Trunking lid screwed on for delivery.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                         |
|--------------|-------------------------------------------------------------------------|
| Catalog path | OBO BETTERMANN > UFS Underfloor piping systems - OBO BETTERMANN > Other |
|--------------|-------------------------------------------------------------------------|

## Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 94,1702 kg CO2e / 1 Meter  
Cover fastening, locking no  
Cover material thickness 4  
Covers 3  
Decouplable no  
Dimension 2400x600x60  
Duct height, min. 60 mm

Floor plate yes  
Height-adjustment range, max. 110 mm  
Height-adjustment range, min. 60 mm  
Installation opening for on-floor tank no  
Length 2400 mm  
Material Steel  
Minimum screed height 60  
Mounting opening Without  
Mounting opening cover no  
Number of compartments 3 St.  
Number of insertable partitions 2  
Number of planned flush-mount units 3  
Removable cover yes  
Seal installation option yes  
Separating retainer fastening Lock  
Suitable for expansion joint no  
Surface Strip galvanized  
Trunking height, max. 110 mm  
Usable cross-section 21000 mm<sup>2</sup>  
Width 600 mm  
With connection opening no  
With equipotential bonding no  
With overhang yes  
With separating retainer no

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / OKA-W6006050 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.