

INDUSTRIAL COMPONENT DATA

OKB U 25085 BD 7403818 OBO BETTERMANN Flushfloor trunking unit with blanking lid, 2000x250x93, Strip-galvani..

Brand: OBO BETTERMANN | Manufacturer Part Number: OKB U 25085 BD



Manufacturer	OBO BETTERMANN
MPN / Reference	OKB U 25085 BD
Catalog number	7403818
Category	Underfloor installation duct flush floor open
Minimum order	2 m.
Document ID	EO-F31DB16F92
Generated	2026-08-02

Product Overview

Flushfloor trunking unit with blanking lid, 2000x250x93, Strip-galvanised, DIN EN 10147, Steel, St

Trunking unit with blanking lid. Ready-to-mount trunking unit for cable routing and device installation, consisting of a trunking base with two blanking covers. The scope of delivery contains two lid butt seals and one connector. For height adjustment, six height adjustment units are required. Load capacity up to a maximum of 5 kN. The trunking unit can be supplemented with an adjustable floor covering contact profile for screed limitation in areas of door frames and in front of radiator niches.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > UFS Underfloor piping systems - OBO BETTERMANN > Other
--------------	---

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 55,8728 kg CO2e / 1 Meter

Cover fastening, locking no

Cross-section, draw a 4231 mm²

Cross-section, draw b 7306 mm²

Decouplable yes

Dimension 2000x273x85

Dimension h 85 mm

Floor care Dry

Floor plate yes

Height 93 mm

Installation opening for on-floor tank no
Length 2000 mm
Material Steel
Minimum screed height 93
Mounting opening Without
Mounting opening cover no
Number of compartments 2 St.
Removable cover yes
Seal installation option no
Separating retainer fastening Plug
Suitable for expansion joint no
Surface Strip galvanized
Vertical load, large area to 5,000 N
Vertical load, small area to 3,000 N
Width 250 mm
With connection opening no
With equipotential bonding no
With overhang yes
With separating retainer no

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / OKB U 25085 BD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.