

INDUSTRIAL COMPONENT DATA

RKFR2 4 SL2V2 20 7409462 OBO BETTERMANN Heavy-duty cassette for tube, 20 kN, ø 215mm, Stainless steel, grade..

Brand: OBO BETTERMANN | Manufacturer Part Number: RKFR2 4 SL2V2 20



Manufacturer	OBO BETTERMANN
MPN / Reference	RKFR2 4 SL2V2 20
Catalog number	7409462
Category	Levelling cassette for duct mounting, raised and underfloor installation
Minimum order	1 Pcs
Document ID	EO-02288E84F2
Generated	2026-07-27

Product Overview

Heavy-duty cassette for tube, 20 kN, ø 215mm, Stainless steel, grade 304, VA, 1.4301

Height-adjustable heavy-duty cassette for tube body RKFRSL, nominal size R4, stainless steel. Round heavy-duty cassette for tube body of nominal size R4 for the installation of accessories in trunking systems, raised and cavity floors, in dry or wet-cleaned floors indoors. Load class 2 to 20 kN. Height-adjustable heavy-duty cassette with tube body with a load bearing capacity of 2-20 kN, 2-compartment. 2 APMT2 cover plates can be installed. For the installation of two UT3 universal supports for four single accessories with support ring/support clamp or six Modul 45 devices. The tube body is not contained in the scope of delivery.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > UFS Underfloor piping systems - OBO BETTERMANN > Other

Additional Product Information

Cable outlet version Lowerable tube body

CO2 Footprint (GWP) Cradle-to-Gate 14,7038 kg CO2e / 1 Piece

Decouplable no

Device support to accept mounting boxes yes

Dimension Ø215mm

Dimension h 110 mm

Floor care Wet

Floor covering thickness 20 mm

Floor height, max. 155 mm

Floor height, min. 110 mm
Heavy load class 20 kN (OBO SL2)
Heavy-duty version yes
Height-adjustment range, max. 155 mm
Height-adjustment range, min. 110 mm
Installation depth 110 mm
Installation diameter 215
Installation system type UT3
Material Stainless steel 1.4301
Nominal size for device installation units R4
Number of cable outlets 1
Number of installable devices 6
Number of mounting boxes 2
Protection rating (IP) when unused IP44
Protection rating (IP) when used IP20
Protection rating IK code IK10
Suitable for cavity floor installation yes
Suitable for raised floor installation yes
Version for Round

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / RKFR2 4 SL2V2 20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.