

INDUSTRIAL COMPONENT DATA

RKFR2 9 SL2V2 20 7409470 OBO BETTERMANN Heavy-duty cassette for tube, 20 kN, ø 305mm, Stainless steel, grade..

Brand: OBO BETTERMANN | Manufacturer Part Number: RKFR2 9 SL2V2 20



Manufacturer	OBO BETTERMANN
MPN / Reference	RKFR2 9 SL2V2 20
Catalog number	7409470
Category	Levelling cassette for duct mounting, raised and underfloor installation
Minimum order	1 Pcs
Document ID	EO-4BD7340398
Generated	2026-07-27

Product Overview

Heavy-duty cassette for tube, 20 kN, ø 305mm, Stainless steel, grade 304, VA, 1.4301

Height-adjustable heavy-duty cassette for tube body RKFRSL, nominal size R9, stainless steel. Round heavy-duty cassette for tube body of nominal size R9 for the installation of accessories in trunking systems, raised and cavity floors, in dry or wet-cleaned floors. Load class 2 to 20 kN. Height-adjustable heavy-duty cassette with tube body with a load bearing capacity of 2-20 kN, 3-compartment. 3 APMT5 cover plates can be installed. For the installation of three UT4 universal supports for nine single accessories with support ring/support clamp or 12 Modul 45 devices. The tube body is not contained in the scope of delivery. Height-adjustable round cassette, 3-compartment, of nominal size 9, for tube bodies. For the installation in trunking systems and in raised and cavity floors in dry- or

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > UFS Underfloor piping systems - OBO BETTERMANN > Other

Additional Product Information

Cable outlet version Lowerable tube body
CO2 Footprint (GWP) Cradle-to-Gate 24,6974 kg CO2e / 1 Piece
Decouplable no
Device support to accept mounting boxes yes
Dimension Ø305mm
Dimension h 110 mm
Floor care Wet
Floor covering thickness 20 mm

Floor height, max. 155 mm
Floor height, min. 110 mm
Heavy load class 20 kN (OBO SL2)
Heavy-duty version yes
Height-adjustment range, max. 155 mm
Height-adjustment range, min. 110 mm
Installation depth 110 mm
Installation diameter 305
Installation system type UT4
Material Stainless steel 1.4301
Nominal size for device installation units R9
Number of cable outlets 1
Number of installable devices 12
Number of mounting boxes 3
Protection rating (IP) when unused IP44
Protection rating (IP) when used IP20
Protection rating IK code IK10
Suitable for cavity floor installation yes
Suitable for raised floor installation yes
Version for Round

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / RKFR2 9 SL2V2 20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.