

INDUSTRIAL COMPONENT DATA

RKR2 4SL2 V2 20 7409072 OBO BETTERMANN Heavy-duty cassette blank, 20 kN, 200x200mm, Stainless steel, grade 3..

Brand: OBO BETTERMANN | Manufacturer Part Number: RKR2 4SL2 V2 20



Manufacturer	OBO BETTERMANN
MPN / Reference	RKR2 4SL2 V2 20
Catalog number	7409072
Category	Levelling cassette for duct mounting, raised and underfloor installation
Minimum order	1 Pcs
Document ID	EO-72DDF7493D
Generated	2026-07-29

Product Overview

Heavy-duty cassette blank, 20 kN, 200x200mm, Stainless steel, grade 304, VA, 1.4301

Height-adjustable heavy-duty cassette, blank, RKRSL, nominal size R4, stainless steel. Round, "blank", heavy-duty cassette of nominal size R4 for the creation of an inspection opening in trunking systems, raised and cavity floors, in dry or wet-care floors for indoor use. Load class 2 to 20 kN. Only suitable for smooth floor coverings. Height-adjustable heavy-duty cassette as a blind cassette with a load bearing capacity of 2-20 kN, 2-compartment. 2 APMT2 cover plates can be installed. For the installation of 2 UT3 universal supports for 4 individual installation devices with support ring/support clamp or 6 Modul 45 devices for indoor use.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > UFS Underfloor piping systems - OBO BETTERMANN > Other

Additional Product Information

Cable outlet version No cable outlet

CO2 Footprint (GWP) Cradle-to-Gate 12,8304 kg CO2e / 1 Piece

Decouplable no

Device support to accept mounting boxes yes

Dimension Ø215mm

Dimension h 105 mm

Floor care Wet

Floor covering thickness 20 mm

Floor height, max. 155 mm

Floor height, min. 105 mm
Heavy load class 20 kN (OBO SL2)
Heavy-duty version yes
Height-adjustment range, max. 155 mm
Height-adjustment range, min. 105 mm
Installation depth 105 mm
Installation diameter 215
Installation system type UT3
Material Stainless steel 1.4301
Nominal size for device installation units R4
Protection rating (IP) when unused IP44
Protection rating (IP) when used IP00
Protection rating IK code IK10
Suitable for cavity floor installation yes
Suitable for raised floor installation yes
Version for Round

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / RKR2 4SL2 V2 20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.