

INDUSTRIAL COMPONENT DATA

RKR2 9M 25 7409124 OBO BETTERMANN Round cassette blank, ø 305mm, Brass, CuZn

Brand: OBO BETTERMANN | Manufacturer Part Number: RKR2 9M 25



Manufacturer	OBO BETTERMANN
MPN / Reference	RKR2 9M 25
Catalog number	7409124
Category	Levelling cassette for duct mounting, raised and underfloor installation
Minimum order	1 Pcs
Document ID	EO-8B709433B1
Generated	2026-08-02

Product Overview

Round cassette blank, ø 305mm, Brass, CuZn
RKR2 9M 25 round cover and frame set, blind Ø305mm Brass, CuZn,
Height-adjustable cassette for inspection opening, RKR, brass. Height-adjustable "blank" cassette for the creation of an inspection opening of nominal size R9 in dry or wet-cleaned floors for indoor use. Only suitable for smooth floor coverings. Height-adjustable cassette as a blind cassette, 3-compartment. 3 APMT5 cover plates can be installed. For the installation of 3 UT4 universal supports for 9 individual installation devices with support ring/support clamp or 12 Modul 45 devices.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **OBO BETTERMANN > UFS Underfloor piping systems - OBO BETTERMANN > Other**

Additional Product Information

Approvals VDE
Cable outlet version No cable outlet
CO2 Footprint (GWP) Cradle-to-Gate 14,7335 kg CO2e / 1 Piece
Decouplable no
Device support to accept mounting boxes no
Dimension Ø305mm
Floor care Wet
Floor covering thickness 25 mm
Floor height, max. 155 mm

Floor height, min. 105 mm
Heavy-duty version no
Height-adjustment range, max. 155 mm
Height-adjustment range, min. 105 mm
Installation depth 105 mm
Installation diameter 305
Installation system type UT4
Length 304 mm
Material Brass
Nominal size for device installation units R9
Number of mounting boxes 3
Protection rating (IP) when unused IP44
Protection rating (IP) when used IP00
Protection rating IK code IK10
Suitable for cavity floor installation yes
Suitable for raised floor installation yes
Version for Round
Vertical load, large area to 5,000 N
Vertical load, small area to 3,000 N
Width 304 mm
ETIM for 7409124 Underfloor trunking and floor boxes (EC002603)
Feature Name
Feature Value
Min. built-in depth (EF005027)
105 mm
Levelling height (EF007999)
105 mm
Floor maintenance (EF004546)
Wet
Model (EF000010)
Round
Material (EF002169)
Brass
Number of conduit outlets (EF004424)
0
Chassis part for device cups (EF004750)
No
Built-in diameter (EF000943)
305 mm
Number of appliances to build in (EF000219)
0
Number of device cups (EF000436)
3

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / RKR2 9M 25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.