

INDUSTRIAL COMPONENT DATA

RKS2 R4 M25 7409254 OBO BETTERMANN Round cassette with cord outlet, Ø 215mm, Brass, CuZn

Brand: OBO BETTERMANN | Manufacturer Part Number: RKS2 R4 M25



Manufacturer	OBO BETTERMANN
MPN / Reference	RKS2 R4 M25
Catalog number	7409254
Category	Levelling cassette for duct mounting, raised and underfloor installation
Minimum order	1 Pcs
Document ID	EO-5352B7A1C3
Generated	2026-08-02

Product Overview

Round cassette with cord outlet, Ø 215mm, Brass, CuZn

Height-adjustable cassette with cord outlet, RKS2, brass. Height-adjustable cassette of nominal size R4 with cord outlet for installation of accessories in dry-care floors for indoor use. Height-adjustable cassette for cord outlet, 2-compartment. 2 APMT2 cover plates can be installed. For the installation of 2 UT3 universal supports for 4 individual installation devices with support ring/support clamp or 6 Modul 45 devices.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > UFS Underfloor piping systems - OBO BETTERMANN > Other

Additional Product Information

Approvals VDE

Cable outlet version Swivellable cord outlet

CO2 Footprint (GWP) Cradle-to-Gate 9,8361 kg CO2e / 1 Piece

Decouplable no

Device support to accept mounting boxes yes

Dimension Ø215mm

Floor care Dry

Floor covering thickness 25 mm

Floor height, max. 155 mm

Floor height, min. 110 mm

Heavy-duty version no

Height-adjustment range, max. 155 mm
Height-adjustment range, min. 110 mm
Installation depth 110 mm
Installation diameter 215
Installation system type UT3
Length 214 mm
Material Brass
Nominal size for device installation units R4
Number of cable outlets 1
Number of installable devices 6
Number of mounting boxes 2
Protection rating (IP) when unused IP40
Protection rating (IP) when used IP20
Protection rating IK code IK10
Suitable for cavity floor installation yes
Suitable for raised floor installation yes
Version for Round
Vertical load, large area to 5,000 N
Vertical load, small area to 3,000 N
Width 214 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / RKS2 R4 M25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.