

INDUSTRIAL COMPONENT DATA

UDHOME4 2V MT V 7427216 OBO BETTERMANN Service outlet, complete with protective contact socket, Stainless st..

Brand: OBO BETTERMANN | Manufacturer Part Number: UDHOME4 2V UT V



Manufacturer	OBO BETTERMANN
MPN / Reference	UDHOME4 2V UT V
Catalog number	7427216
Category	Installation box for underfloor-installation
Minimum order	1 Pcs
Document ID	EO-9953F5668E
Generated	2026-08-03

Product Overview

Service outlet, complete with protective contact socket, Stainless steel, grade 304, VA, 1.4301

UDHOME4 floor box, with universal support UT3 45 3, triple VDE, stainless steel. Square floor box for use in dry-cleaned cavity and screed floors in indoor areas. Installation housing with pre-marked insertion openings for pipes (M25). With two UT3 45 3 universal supports and a triple protective contact socket. Cover adjustable to top edge of floor covering using four height-adjustment supports. The minimum installation depth is 95 mm, the height-adjustment range + 30 mm. Surfaces made of stainless steel and visible in the floor covering.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > UFS Underfloor piping systems - OBO BETTERMANN > Other

Additional Product Information

Cable outlet version Swivellable cord outlet

CO2 Footprint (GWP) Cradle-to-Gate 18,176 kg CO2e / 1 Piece

Cover version Floor covering recess

Equipment 2 UT3, triple VDE socket

Floor covering protection frame no

Floor covering thickness 15 mm

Floor height, max. 125 mm

Floor height, min. 95 mm

Height-adjustment range, max. 125 mm

Height-adjustment range, min. 95 mm

Installation depth 95 mm
Length 202 mm
Length of external dimensions 199 mm
Length of installation dimensions 202 mm
Material Stainless steel 1.4301
Number of mounting boxes 2
Opening mechanism Handle
Protection rating (IP) when unused IP40
Protection rating (IP) when used IP20
Protection rating IK code IK10
Screed height, max. 110 mm
Screed height, min. 95 mm
Suitable for cavity floor installation yes
Suitable for raised floor installation no
Suitable for underfloor ducts no
Suitable for wet care no
Version for Square
Vertical load, large area to 5,000 N
Vertical load, small area to 3,000 N
Wide external dimensions 199 mm
Wide installation dimensions 202 mm
Width 202 mm
With floor covering recess yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / UDHOM4 2V UT V with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.