

INDUSTRIAL COMPONENT DATA

UDHOME9 2V MT V 7427308 OBO BETTERMANN Service outlet, complete with protective contact socket, Stainless st..

Brand: OBO BETTERMANN | Manufacturer Part Number: UDHOME9 2V UT45V



Manufacturer	OBO BETTERMANN
MPN / Reference	UDHOME9 2V UT45V
Catalog number	7427308
Category	Installation box for underfloor-installation
Minimum order	1 Pcs
Document ID	EO-3A259BA547
Generated	2026-08-02

Product Overview

Service outlet, complete with protective contact socket, Stainless steel, grade 304, VA, 1.4301
Floor box UDHOME9, two double VDE, stainless steel. Square floor box for use in dry-cleaned cavity and screed floors in indoor areas. Installation housing with pre-marked insertion openings for pipes (M25). With three UT4 universal supports and two double protective contact sockets. Cover adjustable to top edge of floor covering using four height-adjustment supports. The minimum installation depth is 95 mm, the height-adjustment range + 30 mm. Surfaces visible in the floor covering made of stainless steel.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **OBO BETTERMANN > UFS Underfloor piping systems - OBO BETTERMANN > Other**

Additional Product Information

Cable outlet version Swivellable cord outlet
CO2 Footprint (GWP) Cradle-to-Gate 25,4169 kg CO2e / 1 Piece
Cover version Floor covering recess
Equipment 3 UT4, 2 double VDE socket
Floor covering thickness 15 mm
Floor height, max. 125 mm
Floor height, min. 95 mm
Height-adjustment range, max. 125 mm
Height-adjustment range, min. 95 mm
Length 246 mm

Length of external dimensions 243 mm
Length of installation dimensions 246 mm
Material Stainless steel 1.4301
Opening mechanism Handle
Protection rating (IP) when unused IP40
Protection rating (IP) when used IP20
Protection rating IK code IK10
Screed height, max. 110 mm
Screed height, min. 95 mm
Vertical load, large area to 5,000 N
Vertical load, small area to 3,000 N
Wide external dimensions 243 mm
Wide installation dimensions 246 mm
Width 246 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / UDHOM9 2V UT45V with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.