


INDUSTRIAL COMPONENT DATA

UGD55 250-3 9R 7410060 OBO BETTERMANN Underfloor box empty for GES9/55UV, 367x367x55, Strip-galvanised, DIN ..

Brand: OBO BETTERMANN | Manufacturer Part Number: UGD55 250-3 9R



Manufacturer	OBO BETTERMANN
MPN / Reference	UGD55 250-3 9R
Catalog number	7410060
Category	Service box for underfloor installation
Minimum order	1 Pcs
Document ID	EO-47FE987623
Generated	2026-08-02

Product Overview

Underfloor box empty for GES9/55UV, 367x367x55, Strip-galvanised, DIN EN 10147, Steel, St UGD250-3 underfloor box for GES9/55. Underfloor accessory box with mounting lid and lid blanking plate with sheet steel side walls. For the installation of a square GES9 55 service outlet in screed heights of 55 mm or more. Height can be infinitely adjusted to the nominal screed height and the screed can be worked flush to the screed scraping edge. With 7 x M20, 3 x M25, 4 x M32 pipe insertion openings on each side. Usable pipe size at a system height of 55 mm: M20.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > UFS Underfloor piping systems - OBO BETTERMANN > Other

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 25,7284 kg CO2e / 1 Piece

Cover version Square

Decouplable no

Dimension 367x367x55

Dimension a 244 mm

Dimension A 367 mm

Dimension b 244 mm

Dimension B 367 mm

Dimension h 55 mm

Expansion option For installation of accessories

Floor care Dry

Floor plate yes
For pipe connection yes
Height-adjustment range, max. 80 mm
Height-adjustment range, min. 55 mm
Installation opening for flush-mount unit Square
Installation opening for on-floor tank no
Lowerable to be flush-floor yes
Material Steel
Nominal size 250 mm
Nominal size for device installation units 9
Screed height, max. 80 mm
Screed height, min. 55 mm
Seal installation option no
Suitable for screed-covered underfloor ducts no
Suitable for screed-flush closed underfloor ducts no
Suitable for underfloor ducts no
Surface Strip galvanized
Trunking width, max. 250 mm
Trunking width, min. 190 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / UGD55 250-3 9R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.