

INDUSTRIAL COMPONENT DATA

V10 COMPACT 150 5093378 OBO BETTERMANN V10 COMPACT V10 COMPACT 150

Brand: OBO BETTERMANN | Manufacturer Part Number: V10 COMPACT 150



Manufacturer	OBO BETTERMANN
MPN / Reference	V10 COMPACT 150
Catalog number	5093378
Category	Surge protection device for power supply systems
Minimum order	1 Pcs
Document ID	EO-662D737BBD
Generated	2026-07-31

Product Overview

V10 COMPACT V10 COMPACT 150

V10 Compact V10 COMPACT 150, 150V,

Surge arrester V10 Compact 150 V. Surge protective device, compact module, type 2+3• Surge protection in sub-distributors to VDE 0100-443 (IEC 60364-4-44)• Arresting capacity up to 60 kA (8/20) in total• Integrated 3+1 solution for TN and TT network systems on 45 mm module width • High-performance varistor technology• Incl. thermal and dynamic cut-off unit and visual function displayApplication: Sub/storey distribution as well as device protection in rotational current systems.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN

Additional Product Information

Arrester surge current (8/20 μ s) [total] 60 kA

Blow-out no

CO2 Footprint (GWP) Cradle-to-Gate 0,7051 kg CO₂e / 1 PieceConductor cross-section, rigid (single-wire/multiwire), max. 10 mm²Conductor cross-section, rigid (single-wire/multiwire), min. 2,5 mm²

Dimension 150V

Follow current quenching capacity (eff) [N-PE] 0,1 kA

Installation type DIN rail 35 mm

Integrated back-up fuse no

Lightning protection zone LPZ 1->3
Max. mains-side overcurrent protection 63
Maximum back-up fuse 63 A
Maximum continuous voltage AC 150 V
Maximum discharge current (8/20 us) 20 kA
Network form Other
Nominal discharge current (8/20 μs) 10 kA
Nominal voltage AC (50/60 Hz) 120 V
Operating temperature, max. 80 °C
Operating temperature, min. -40 °C
Permitted temperature range, max. 80 °C
Permitted temperature range, min. -40 °C
Pole version 3+N/PE
Protection rating IP20
Remote signalling no
Response time

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / V10 COMPACT 150 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.