

**INDUSTRIAL COMPONENT DATA**

# 106 FL M25 9 39 2013009 OBO BETTERMANN Flat cable threaded connection , M25, Stone grey, 7030, Polyethylene,...

Brand: OBO BETTERMANN | Manufacturer Part Number: 106 FL M25 9 39



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | OBO BETTERMANN  |
| MPN / Reference | 106 FL M25 9 39 |
| Catalog number  | 2013009         |
| Category        | Cable gland     |
| Minimum order   | 25 Pcs          |
| Document ID     | EO-4519111B1B   |
| Generated       | 2026-08-02      |

## Product Overview

Flat cable threaded connection , M25, Stone grey, 7030, Polyethylene, PE

Flat cable threaded connection, metric thread M25, stone grey. Flat-cable entry, choke-nipple design with metric connecting thread to IEC 432, protection rating IP31, with pre-mounted support sealing ring 107/F.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                                      |
|--------------|--------------------------------------------------------------------------------------|
| Catalog path | OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > GIs Plastic |
|--------------|--------------------------------------------------------------------------------------|

## Additional Product Information

Bend protection yes

CO2 Footprint (GWP) Cradle-to-Gate 0,0767 kg CO2e / 1 Piece

Colour Stone grey; RAL 7030

Dimension M25

Dimension A 30 mm

Dimension B 56 mm

Dimension D 35 mm

Dimension G M25 mm

Dimension L 52 mm

Dimension L1 12 mm

Dimension L2 40 mm

explosion-proof no

Fibre-glass reinforced no

Flat cable gland yes  
Flat cable/width, max. 39 mm  
Flat cable/width, min. 36 mm  
Flat cables/thickness, max. 9 mm  
Flat cables/thickness, min. 7 mm  
For Ex zone Without  
Impact-resistant no  
Material Polyethylene  
Protection rating IP31  
Sealing insert, multiple no  
Strain relief option no  
Thread M25  
Thread type Metric  
Type of seal Sealing ring  
Version for Straight  
With locknut no

### REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 106 FL M25 9 39 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

#### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.