


INDUSTRIAL COMPONENT DATA

107 R PG42-29 PA 2030837 OBO BETTERMANN Reduction , PG42-PG29, Light grey, 7035, Polyamide, PA

Brand: OBO BETTERMANN | Manufacturer Part Number: 107 R PG42-29 PA



Manufacturer	OBO BETTERMANN
MPN / Reference	107 R PG42-29 PA
Catalog number	2030837
Category	Enlargement/reducing ring
Minimum order	25 Pcs
Document ID	EO-42FE08A29E
Generated	2026-08-03

Product Overview

Reduction , PG42-PG29, Light grey, 7035, Polyamide, PA

Reduction, PG thread. Reduction with PG internal and external thread to DIN 40430 for mounting plastic cable glands on enclosures. Protection class IP54 without additional connecting seal. Protection class up to IP68 possible with additional connecting seal, e.g. O-ring or flat sealing ring.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > GIs Plastic

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 0,1266 kg CO2e / 1 Piece

Colour Light grey; RAL 7035

Dimension PG42-PG29

Dimension D 27,5 mm

Dimension E 59 mm

Dimension L1 18 mm

Dimension L2 6 mm

Dimension L3 19,5 mm

explosion-proof no

Halogen-free yes

Material Polyamide

Nickel-plated no

Thread dimension, PG, external 42

Thread dimension, PG, internal 29

Thread length 18 mm

Thread type: External thread PG

Thread type: Internal thread PG

WAF 55

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 107 R PG42-29 PA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.