

INDUSTRIAL COMPONENT DATA

90 M16 GE 2032380 OBO BETTERMANN Screw-in nipple closed version, M16, Light grey, 7035, Polyethylene, PE

Brand: OBO BETTERMANN | Manufacturer Part Number: 90 M16 GE



Manufacturer	OBO BETTERMANN
MPN / Reference	90 M16 GE
Catalog number	2032380
Category	Cable plug sealing clamp
Minimum order	100 Pcs
Document ID	EO-D2C770219F
Generated	2026-08-02

Product Overview

Screw-in nipple closed version, M16, Light grey, 7035, Polyethylene, PE

Screw-in nipple, metric thread, with perforation membrane. With perforation membranes, the opening D is pre-marked, but closed. Grip seal to screw into metric thread to IEC 423. With self-sealing cone at the end of the thread, therefore no connection thread sealing ring required. Protection rating achievable with careful mounting: IP54. With perforation membranes, the opening D is pre-marked, but closed.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > GIs Plastic

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 0,0042 kg CO2e / 1 Piece

Colour Light grey; RAL 7035

Dimension M16

Dimension D 5 mm

Dimension E 20 mm

Dimension L1 8 mm

Dimension L2 6 mm

Halogen-free yes

Material Polyethylene

Protection rating IP54

Size M16

Thread length 8 mm

WAF 16

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 90 M16 GE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.