

INDUSTRIAL COMPONENT DATA

V-TEC L PG29 LGR 2024349 OBO BETTERMANN Cable gland with long connection thread, PG29, Light grey, 7035, Pol..

Brand: OBO BETTERMANN | Manufacturer Part Number: V-TEC L PG29 LGR



Manufacturer	OBO BETTERMANN
MPN / Reference	V-TEC L PG29 LGR
Catalog number	2024349
Category	Cable gland
Minimum order	20 Pcs
Document ID	EO-EE857D2B6C
Generated	2026-08-02

Product Overview

Cable gland with long connection thread, PG29, Light grey, 7035, Polyamide, PA

Cable gland, long PG thread, light grey. Cable gland with PG connection thread in cap nut design, suitable for junction boxes, housings, distributor boxes in private and industrial areas. With strain relief and integrated sealing lip, tested according to DIN EN 62444. Protection class IP68. Can be used between -20°C and +65°C.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > GIs Plastic

Additional Product Information

Bend protection no
 CO2 Footprint (GWP) Cradle-to-Gate 0,1809 kg CO2e / 1 Piece
 Colour Light grey; RAL 7035
 Dimension PG29
 Dimension E 47,5 mm
 Dimension L max. 43 mm
 Dimension L min. 32 mm
 Dimension L1 15 mm
 Dimension L2 7 mm
 Dimension L3 24,5 mm
 explosion-proof no
 Fibre-glass reinforced no

Flat cable gland no
For Ex zone Without
For Ex zone dust Without
For Ex zone gas Without
Halogen-free yes
Hexagonal corner dimension 47,5 mm
Impact-resistant no
Material Polyamide
Nominal thread size 29
Permitted temperature range, max. 65 °C
Permitted temperature range, min. -20 °C
Protection rating IP68
Sealing area D, max. 25 mm
Sealing area D, min. 14 mm
Sealing insert, multiple no
Splittable gland no
Strain relief option yes
Thread Pg 29
Thread increase 1,5 mm
Thread length 15 mm
Thread type PG
Type of seal Sealing ring
Unstable torque 5 Nm
Version for Straight
WAF 42
With locknut no

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / V-TEC L PG29 LGR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.