

INDUSTRIAL COMPONENT DATA

V-TEC PG7+ LGR 2024655 OBO BETTERMANN Cable gland with locknut, PG7, Light grey, 7035, Polyamide, PA

Brand: OBO BETTERMANN | Manufacturer Part Number: V-TEC PG7+ LGR



Manufacturer	OBO BETTERMANN
MPN / Reference	V-TEC PG7+ LGR
Catalog number	2024655
Category	Cable gland
Minimum order	50 Pcs
Document ID	EO-392BA4D7B5
Generated	2026-08-01

Product Overview

Cable gland with locknut, PG7, Light grey, 7035, Polyamide, PA

Cable gland, PG thread, set with locknut, light grey. Cable gland with PG connection thread in cap nut design, suitable for junction boxes, housings, distributor boxes in private and industrial areas. With strain relief and integrated sealing lip, tested according to DIN EN 62444. Protection class IP68. Can be used between -20°C and +65°C. Including locknut. Table column D1: sealing range to VDE 0619, in which no strain relief is required. Table column D2: Sealing range including strain relief and twist protection to VDE 0619

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > GIs Plastic
--------------	--

Additional Product Information

Bend protection no

CO2 Footprint (GWP) Cradle-to-Gate 0,03 kg CO2e / 1 Piece

Colour Light grey; RAL 7035

Dimension PG7

Dimension E1 (mm) 16,5 mm

Dimension E2 21 mm

Dimension L max. 23 mm

Dimension L min. 18 mm

Dimension L1 8 mm

Dimension L2 5 mm

Dimension L3 5 mm
explosion-proof no
Fibre-glass reinforced no
Flat cable gland no
For Ex zone Without
For Ex zone dust Without
For Ex zone gas Without
Halogen-free yes
Hexagonal corner dimension 16,5 mm
Impact-resistant no
Material Polyamide
Nominal thread size 7
Permitted temperature range, max. 65 °C
Permitted temperature range, min. -20 °C
Protection rating IP68
Sealing area D, max. 6,5 mm
Sealing area D, min. 2,5 mm
Sealing insert, multiple no
Splittable gland no
Strain relief option yes
Thread Pg 7
Thread increase 1,5 mm
Thread length 8 mm
Thread type PG
Type of seal Sealing ring
Version for Straight
WAF 1 15 mm
WAF 2 19 mm
With locknut yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / V-TEC PG7+ LGR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.