

INDUSTRIAL COMPONENT DATA

V-TEC VM L25 LGR 2022949 OBO BETTERMANN Cable gland fully metric long, M25, Light grey, 7035, Polyamide, PA

Brand: OBO BETTERMANN | Manufacturer Part Number: V-TEC VM L25 LGR



Manufacturer	OBO BETTERMANN
MPN / Reference	V-TEC VM L25 LGR
Catalog number	2022949
Category	Cable gland
Minimum order	25 Pcs
Document ID	EO-4DF7D26823
Generated	2026-08-02

Product Overview

Cable gland fully metric long, M25, Light grey, 7035, Polyamide, PA

V-TEC VM L25 LGR cable gland, long total metric M25 Polyamide, PA,

Cable gland, EX zone, long metric thread, light grey. Cable glands with metric connection thread type with cap nut, for junction boxes, housing, control cabinets in the private and industrial sector. With traction relief and integrated sealing lip, tested according to DIN EN 62444. IP68 protection class. It can be used between -20°C and +65°C.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > GIs Plastic

Additional Product Information

The quickest and most convenient way of providing strain relief and tightness with cable glands on junction boxes and housings is with the tried-and-trusted V-TEC VM cable glands from OBO. With the integrated sealing lip and the special OBO lamella technology protection class IP68 is achieved. Strain relief and tightness have been tested to DIN en 50262. The connecting threads are metric and are therefore suitable for universal use. Eleven screwed in place, the fitting is there for ever, as the optimum thread adjustment with the right pitch ensures permanent resistance to shaking.

Applications: From private housing with junction boxes up to industrial applications in the distributor cabinet.

Temperature range: -20 °C to +65 °C.

ETIM for 2022949 Cable glands and cable entry products (EC000441)

Feature Name

Feature Value

Thread type (EF001758)

Metric

Nominal thread size metric/PG (EF007839)

25

Pitch thread (EF003712)

1.5 mm

Thread length (EF000368)

15 mm

Wrench width (EF000177)

29 mm

Hexagon angular dimension (EF005268)

32 mm

Suitable for cable diameter (EF005466)

9 mm

Material (EF002169)

Plastic

Material quality (EF001257)

Polyamide (PA)

Halogen free (EF000025)

Yes

Degree of protection (IP) (EF005474)

IP68

Shock resistant (EF000084)

No

Colour (EF000007)

Grey

RAL-number (EF000116)

7035

Bend radius protection/trumpet flare (EF000734)

No

With locknut (EF005049)

No

Model (EF000010)

Straight

Multi seal area (EF005004)

No

Flat cable coupling (EF004685)

No

With strain relief (EF0008...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / V-TEC VM L25 LGR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.