

**INDUSTRIAL COMPONENT DATA**

# V-TEC VM L40 LGR 2022953 OBO BETTERMANN Cable gland fully metric long, M40, Light grey, 7035, Polyamide, PA

Brand: OBO BETTERMANN | Manufacturer Part Number: V-TEC VM L40 LGR



|                 |                  |
|-----------------|------------------|
| Manufacturer    | OBO BETTERMANN   |
| MPN / Reference | V-TEC VM L40 LGR |
| Catalog number  | 2022953          |
| Category        | Cable gland      |
| Minimum order   | 10 Pcs           |
| Document ID     | EO-A7E228CABE    |
| Generated       | 2026-08-02       |

## Product Overview

Cable gland fully metric long, M40, Light grey, 7035, Polyamide, PA

Cable gland, metric thread, long, light grey. Cable gland with metric connection thread in cap nut design, suitable for junction boxes, housings, distributor cabinets in private and industrial areas. With strain relief and integrated sealing lip, tested according to DIN EN 62444. Protection class IP68. Can be used between -20°C and +65°C.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                                      |
|--------------|--------------------------------------------------------------------------------------|
| Catalog path | OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > GIs Plastic |
|--------------|--------------------------------------------------------------------------------------|

## Additional Product Information

Bend protection no

CO2 Footprint (GWP) Cradle-to-Gate 0,1861 kg CO2e / 1 Piece

Colour Light grey; RAL 7035

Dimension M40

Dimension E 50 mm

Dimension L max. 46 mm

Dimension L min. 32 mm

Dimension L1 18 mm

Dimension L2 7 mm

explosion-proof no

Fibre-glass reinforced no

Flame-resistant acc. to VDE 0471/DIN 695 Part 2-1, test temperature 650°C

Flat cable gland no  
For Ex zone Without  
For Ex zone dust Without  
For Ex zone gas Without  
Halogen-free yes  
Hexagonal corner dimension 50 mm  
Impact-resistant no  
Material Polyamide  
Nominal thread size 40  
Permitted temperature range, max. 65 °C  
Permitted temperature range, min. -20 °C  
Protection rating IP68  
Sealing area D, max. 28 mm  
Sealing area D, min. 16 mm  
Sealing insert, multiple no  
Splittable gland no  
Strain relief option yes  
Thread M40 x 1,5  
Thread increase 1,5 mm  
Thread length 18 mm  
Thread type Metric  
Type of seal Sealing ring  
Unstable torque 10 Nm  
Version for Straight  
WAF 44  
With locknut no

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / V-TEC VM L40 LGR with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.