

**INDUSTRIAL COMPONENT DATA**

# 2061 2M FS 1107127 OBO BETTERMANN Profile rails unperforated, slot width 11 mm, 2000x25x10, Strip-galvanised..

Brand: OBO BETTERMANN | Manufacturer Part Number: CL2510UP2000FS



|                 |                        |
|-----------------|------------------------|
| Manufacturer    | OBO BETTERMANN         |
| MPN / Reference | CL2510UP2000FS         |
| Catalog number  | 1107127                |
| Category        | Mounting rail/-profile |
| Minimum order   | 2 m.                   |
| Document ID     | EO-C57FFF0D9E          |
| Generated       | 2026-07-31             |

## Product Overview

Profile rails unperforated, slot width 11 mm, 2000x25x10, Strip-galvanised, DIN EN 10147, Steel, St CL2510 profile rail, slot 11 mm, FS, unperforated. Light-duty C profile rail for cable routing, in conjunction with series clips or clamp clips with N foot. Can also be used in building of control cabinets.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                                               |
|--------------|-----------------------------------------------------------------------------------------------|
| Catalog path | OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > Installation Profile |
|--------------|-----------------------------------------------------------------------------------------------|

## Additional Product Information

Breakable no  
Bundle 50 m  
CO2 Footprint (GWP) Cradle-to-Gate 0,9251 kg CO2e / 1 Meter  
Dimension 2000x25x10  
Dimension L 2000 mm  
Height 10 mm  
Length 2000 mm  
Maintain electrical functions no  
Material Steel  
Material thickness 1 mm  
Profile shape C profile

Slot width 11 mm  
Static value A 0,52 cm<sup>2</sup>  
Static value Iy 0,08 cm<sup>4</sup>  
Static value Iz 0,44 cm<sup>4</sup>  
Static value Wy 0,13 cm<sup>3</sup>  
Static value Wz 0,35 cm<sup>3</sup>  
Surface Strip galvanized  
Type of perforation Without  
Version for Single profile  
Width 25 mm  
With perforation no  
With toothing no

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / CL2510UP2000FS with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.