

INDUSTRIAL COMPONENT DATA

CL2510P2000FS 1108123 OBO BETTERMANN Profile rails perforated, slot width 11 mm, 2000x25x10, Strip-galvanise..

Brand: OBO BETTERMANN | Manufacturer Part Number: CL2510P2000FS



Manufacturer	OBO BETTERMANN
MPN / Reference	CL2510P2000FS
Catalog number	1108123
Category	Mounting rail/-profile
Minimum order	2 m.
Document ID	EO-966D4E6F79
Generated	2026-07-31

Product Overview

Profile rails perforated, slot width 11 mm, 2000x25x10, Strip-galvanised, DIN EN 10147, Steel, St
Profile CL2510P2000FS, perfor., slot width 11mm 2000x25x10 Steel, St, strip galvanized, DIN EN 10346
CL2510 profile, 11 mm groove, FS, perforated. C-profile for light wiring loads, in combination with multi-pipe clamps or profile clamps with N-type pins. It is also used in the assembly of control cabinets.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > Installation Profile
--------------	---

Additional Product Information

C-profile for light wiring loads, in combination with multi-pipe clamps or profile clamps with N-type pins. It is also used in the assembly of control cabinets.

ETIM for 1108123 Fixings and fasteners (EC000386)

Feature Name

Feature Value

Length (EF001438)

2000 mm

Width (EF000008)

25 mm

Height (EF000040)

10 mm

Material thickness (EF000386)

1 mm

Profile shape (EF005179)

C-profile

Type of perforation (EF004147)

Slotted

With toothing (EF000571)

No

Area moment of inertia I_y (EF012513)

0.06 cm⁴

Area of inertia I_z (EF012514)

0.44 cm⁴

Moment of resistance W_y (EF012503)

0.12 cm³

Moment of resistance W_z (EF012504)

0.35 cm³

Suitable for circuit integrity (EF007806)

No

Material (EF002169)

Steel

Surface protection (EF000139)

Pre-galvanised

Weight (EF000167)

0.37 kg

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / CL2510P2000FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.