

INDUSTRIAL COMPONENT DATA

2062 2M FT 1109022 OBO BETTERMANN Profile rails unperforated, slot width 12 mm, 2000x27x12,5, Hot-dip galvan..

Brand: OBO BETTERMANN | Manufacturer Part Number: CL2712UP2000FT



Manufacturer	OBO BETTERMANN
MPN / Reference	CL2712UP2000FT
Catalog number	1109022
Category	Mounting rail/-profile
Minimum order	2 m.
Document ID	EO-C95A24F1C4
Generated	2026-08-01

Product Overview

Profile rails unperforated, slot width 12 mm, 2000x27x12,5, Hot-dip galvanised, DIN EN ISO 1461, Steel, St
Profile rail CL2712, slot 12 mm, FT, unperforated. Light-duty C profile rail for cable routing, in conjunction with series clips or clamp clips with N foot. Can also be used in building of control cabinets.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > Installation Profile**

Additional Product Information

Breakable no
Bundle 20 m
CO2 Footprint (GWP) Cradle-to-Gate 1,8227 kg CO2e / 1 Meter
Dimension 2000x27x12,5
Dimension L 2000 mm
Height 12,5 mm
Length 2000 mm
Maintain electrical functions no
Material Steel
Material thickness 2 mm
Profile shape C profile

Slot width 12 mm
Static value A 1,08 cm²
Static value Iz 0,98 cm⁴
Surface Hot-dip galvanised
Type of perforation Without
Version for Single profile
Width 27 mm
With perforation no
With toothing no

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / CL2712UP2000FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.