

INDUSTRIAL COMPONENT DATA

2068 L 2M FT 1119656 OBO BETTERMANN Profile rails perforated, slot width 16.5 mm, 2000x35x18, Hot-dip galvan..

Brand: OBO BETTERMANN | Manufacturer Part Number: AML3518P2000FT



Manufacturer	OBO BETTERMANN
MPN / Reference	AML3518P2000FT
Catalog number	1119656
Category	Mounting rail/-profile
Minimum order	20 m.
Document ID	EO-A1A8A463D0
Generated	2026-08-02

Product Overview

Profile rails perforated, slot width 16.5 mm, 2000x35x18, Hot-dip galvanised, DIN EN ISO 1461, Steel, St Anchor rail AML3518, slot width 16.5 mm, FT, perforated. Central C profile rail for cable routing, in conjunction with clamp clips with a hammerhead foot. Can also be used as suspension construction for cable support systems.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > Installation Profile

Additional Product Information

Breakable no
Bundle 20 m
CO2 Footprint (GWP) Cradle-to-Gate 1,9412 kg CO2e / 1 Meter
Dimension 2000x35x18
Dimension L 2000 mm
Drill hole spacing, centre 50 mm
Height 18 mm
Length 2000 mm
Maintain electrical functions yes
Material Steel
Material thickness 1,5 mm
Profile shape C profile
Slot width 16,5 mm

Static value A 1,01 cm²
Static value Iy 0,44 cm⁴
Static value Iz 1,84 cm⁴
Static value Wy 0,42 cm³
Static value Wz 1,05 cm³
Surface Hot-dip galvanised
Type of perforation Perforated back
Version for Single profile
Width 35 mm
With perforation yes
With tothing no

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / AML3518P2000FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.