

INDUSTRIAL COMPONENT DATA

MS4022P6000FT 1121898 OBO BETTERMANN Profile rails perforated, slot width 18 mm, 6000x40x22,5, Hot-dip galva..

Brand: OBO BETTERMANN | Manufacturer Part Number: MS4022P6000FT



Manufacturer	OBO BETTERMANN
MPN / Reference	MS4022P6000FT
Catalog number	1121898
Category	Mounting rail/-profile
Minimum order	6 m.
Document ID	EO-91C01E9B05
Generated	2026-08-02

Product Overview

Profile rails perforated, slot width 18 mm, 6000x40x22,5, Hot-dip galvanised, DIN EN ISO 1461, Steel, St
Profile MS4022P6000FT, perfor., slot width 18mm 6000x40x22.5 Steel, St, Hot dip galvanized, DIN EN ISO 1461
MS4022 mounting rail, heavy duty, slot 18 mm, FT, perforated. Heavy-duty C profile rail for individual installation of support constructions, e.g. for cable trays or as a panel for switchgear cabinets. Can also be used for cable routing, in conjunction with clamp clips with a U foot.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > Installation Profile**

Additional Product Information

Breakable no
CO2 Footprint (GWP) Cradle-to-Gate 3,3077 kg CO2e / 1 Meter
Dimension 6000x40x22,5
Dimension L 6000 mm
Drill hole spacing, centre 50 mm
Height 22,5 mm
Length 6000 mm
Maintain electrical functions no
Material Steel
Material thickness 2 mm
Profile shape C profile

Slot width 18 mm
Static value A 1,74 cm²
Static value I_y 1,18 cm⁴
Static value I_z 4,45 cm⁴
Static value W_y 1,05 cm³
Static value W_z 2,23 cm³
Surface Hot-dip galvanised
Type of perforation Perforated back
Version for Single profile
Width 40 mm
With perforation yes
With toothing no
ETIM for 1121898 Fixings and fasteners (EC000386)
Feature Name
Feature Value
Length (EF001438)
6000 mm
Width (EF000008)
40 mm
Height (EF000040)
22.5 mm
Material thickness (EF000386)
2 mm
Profile shape (EF005179)
C-profile
Type of perforation (EF004147)
Slotted
With toothing (EF000571)
No
Area moment of inertia I_y (EF012513)
1.18 cm⁴
Area of inertia I_z (EF012514)
4.45 cm⁴
Moment of resistance W_y (EF012503)
1.05 cm³
Moment of resistance W_z (EF012504)
2.23 cm³
Suitable for circuit integrity (EF007806)
No
Material (EF002169)
Steel
Surface protection (EF000139)
Hot dip galvanized
Weight (EF000167)
1.53 kg

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / MS4022P6000FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.