

INDUSTRIAL COMPONENT DATA

162 MS PG13.5 2082527 OBO BETTERMANN Cable gland with cutting ring, PG13,5, Nickel-plated, Brass, CuZn

Brand: OBO BETTERMANN | Manufacturer Part Number: 162 MS PG13.5



Manufacturer	OBO BETTERMANN
MPN / Reference	162 MS PG13.5
Catalog number	2082527
Category	Cable gland
Minimum order	50 Pcs
Document ID	EO-CCDAACAF8E
Generated	2026-08-01

Product Overview

Cable gland with cutting ring, PG13,5, Nickel-plated, Brass, CuZn

Cable gland 162 MS PG13.5, with sectional gasket PG13.5 Brass, CuZn, nickel-plated

Cone cable gland, PG thread, cutting ring, nickel-plated. Cable gland with hexagonal intermediate connector, shape C4, to DIN 46320 with Pg connection thread to DIN 40430. Pressure rings made of electrogalvanised and transparently passivated steel. NR/SBR sealing ring. Protection rating: with connection thread sealing ring IP 65, without connection thread sealing ring IP 54. With cutting ring.* Prices according to DEL notation.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > metal GIs
--------------	--

Additional Product Information

Bend protection no

CO2 Footprint (GWP) Cradle-to-Gate 0,0991 kg CO2e / 1 Piece

Dimension PG13,5

Dimension E 24,4 mm

Dimension L 18 mm

Dimension L max. 18 mm

Dimension L1 6,5 mm

Dimension L2 12,5 mm

Dimension L3 3 mm

explosion-proof no

Fibre-glass reinforced no
Flat cable gland no
For Ex zone Without
Halogen-free no
Impact-resistant no
Material Brass
Protection rating IP54
Sealing area D, max. 13,5 mm
Sealing area D, min. 7,5 mm
Sealing insert, multiple no
Strain relief option no
Surface Nickel-plated
Thread Pg 13,5
Thread length 6,5 mm
Thread type PG
Type of seal Cuttable sealing ring
WAF 1 22 mm
WAF 2 20 mm
With locknut no
ETIM for 2082527 Cable glands and cable entry products (EC000441)
Feature Name
Feature Value
Thread type (EF001758)
PG
Thread length (EF000368)
6.5 mm
Suitable for cable diameter (EF005466)
7.5 mm
Material (EF002169)
Metal
Material quality (EF001257)
Brass
Surface protection (EF000139)
Nickel-plated
Halogen free (EF000025)
No
Degree of protection (IP) (EF005474)
IP54
Shock resistant (EF000084)
No
Bend radius protection/trumpet flare (EF000734)
No
With locknut (EF005049)
No
Multi seal area (EF005004)
No
Flat cable coupling (EF004685)

No
With strain relief (EF000878)
No
Type of sealing (EF001217)
Cut-out ring
Explosion-tested version (EF004191)
No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 162 MS PG13.5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.