

INDUSTRIAL COMPONENT DATA

V-TEC L PG13 MS 2085755 OBO BETTERMANN Cable gland with long connection thread, PG13,5, Nickel-plated, Brass..

Brand: OBO BETTERMANN | Manufacturer Part Number: V-TEC L PG13 MS



Manufacturer	OBO BETTERMANN
MPN / Reference	V-TEC L PG13 MS
Catalog number	2085755
Category	Cable gland
Minimum order	50 Pcs
Document ID	EO-88FCB4243F
Generated	2026-08-01

Product Overview

Cable gland with long connection thread, PG13,5, Nickel-plated, Brass, CuZn

Cable gland, long threaded, PG13.5Brass, CuZn, nickel-plated

Cap nut cable gland, PG thread, long, nickel-plated. Cable gland of cap-nut design with large sealing area, and strain relief and torsion protection for high sealing demands with long Pg connection thread to DIN 40430, for thicker housing wall thicknesses in connection with locknut. Polyamide terminal insert. Sealing ring of chloroprene/nitrile rubber. O ring pre-mounted on connection thread. Protection rating IP 68 at 5 bar: 1 hr. Tested to DIN EN 62444. With long connection thread. * Prices according to DEL notation.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > metal GIs

Additional Product Information

Bend protection no

CO2 Footprint (GWP) Cradle-to-Gate 0,1151 kg CO2e / 1 Piece

Dimension PG13,5

Dimension E 24,4 mm

Dimension L max. 25 mm

Dimension L1 10 mm

Dimension L2 3,5 mm

Dimension L3 16 mm

explosion-proof no

Fibre-glass reinforced no
Flat cable gland no
For Ex zone Without
For Ex zone dust Without
For Ex zone gas Without
Halogen-free no
Impact-resistant no
Material Brass
Nominal thread size 13,5
Permitted temperature range, max. 100 °C
Permitted temperature range, min. -20 °C
Protection rating IP68
Sealing area D, max. 12 mm
Sealing area D, min. 5 mm
Sealing insert, multiple no
Splittable gland no
Strain relief option yes
Surface Nickel-plated
Thread Pg 13,5
Thread length 10 mm
Thread type PG
Type of seal Sealing ring
Version for Straight
WAF 22
With locknut no

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / V-TEC L PG13 MS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.