

**INDUSTRIAL COMPONENT DATA**

# V-TEC PG29 MS 2085674 OBO BETTERMANN Cable gland , PG29, Nickel-plated, Brass, CuZn

Brand: OBO BETTERMANN | Manufacturer Part Number: V-TEC PG29 MS



|                 |                |
|-----------------|----------------|
| Manufacturer    | OBO BETTERMANN |
| MPN / Reference | V-TEC PG29 MS  |
| Catalog number  | 2085674        |
| Category        | Cable gland    |
| Minimum order   | 20 Pcs         |
| Document ID     | EO-4A38038A75  |
| Generated       | 2026-07-31     |

## Product Overview

Cable gland , PG29, Nickel-plated, Brass, CuZn

Cap nut cable gland, PG thread, nickel-plated. Cable gland of cap-nut design with large sealing area, and strain relief and torsion protection for high sealing demands with Pg connection thread to DIN 40430, polyamide terminal insert, sealing ring of chloroprene/nitrile rubber, with pre-mounted O ring on the connection thread. Protection rating IP 68 at 5 bar: 1 hr, tested to DIN EN 62444. "Normal" connection thread length, according to DIN 46320. \* Prices according to DEL notation.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > metal GIs

## Additional Product Information

Bend protection no

CO2 Footprint (GWP) Cradle-to-Gate 0,3759 kg CO2e / 1 Piece

Dimension PG29

Dimension E 43,5 mm

Dimension L max. 39 mm

Dimension L1 8 mm

Dimension L2 5 mm

Dimension L3 23,5 mm

explosion-proof no

Fibre-glass reinforced no

Flat cable gland no

For Ex zone Without  
For Ex zone dust Without  
For Ex zone gas Without  
Halogen-free no  
Impact-resistant no  
Material Brass  
Nominal thread size 29  
Permitted temperature range, max. 100 °C  
Permitted temperature range, min. -20 °C  
Protection rating IP68  
Sealing area D, max. 25 mm  
Sealing area D, min. 14 mm  
Sealing insert, multiple no  
Splittable gland no  
Strain relief option yes  
Surface Nickel-plated  
Thread Pg 29  
Thread length 8 mm  
Thread type PG  
Type of seal Sealing ring  
Version for Straight  
WAF 40  
With locknut no

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / V-TEC PG29 MS with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.