

INDUSTRIAL COMPONENT DATA

V-TEC PG9 MS 2085615 OBO BETTERMANN Cable gland , PG9, Nickel-plated, Brass, CuZn

Brand: OBO BETTERMANN | Manufacturer Part Number: V-TEC PG9 MS



Manufacturer	OBO BETTERMANN
MPN / Reference	V-TEC PG9 MS
Catalog number	2085615
Category	Cable gland
Minimum order	50 Pcs
Document ID	EO-CB6C7C8152
Generated	2026-07-31

Product Overview

Cable gland , PG9, Nickel-plated, Brass, CuZn

Cap nut cable gland, PG thread, nickel-plated. Cable gland of cap-nut design with large sealing area, and strain relief and torsion protection for high sealing demands with Pg connection thread to DIN 40430, polyamide terminal insert, sealing ring of chloroprene/nitrile rubber, with pre-mounted O ring on the connection thread. Protection rating IP 68 at 5 bar: 1 hr, tested to DIN EN 62444. "Normal" connection thread length, according to DIN 46320. * Prices according to DEL notation.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > metal GIs

Additional Product Information

Bend protection no
 CO2 Footprint (GWP) Cradle-to-Gate 0,0743 kg CO2e / 1 Piece
 Dimension PG9
 Dimension E 18,9 mm
 Dimension L max. 22 mm
 Dimension L1 6 mm
 Dimension L2 3 mm
 Dimension L3 14 mm
 explosion-proof no
 Fibre-glass reinforced no
 Flat cable gland no

For Ex zone Without
For Ex zone dust Without
For Ex zone gas Without
Halogen-free no
Impact-resistant no
Material Brass
Nominal thread size 9
Permitted temperature range, max. 100 °C
Permitted temperature range, min. -20 °C
Protection rating IP68
Sealing area D, max. 8 mm
Sealing area D, min. 2,5 mm
Sealing insert, multiple no
Splittable gland no
Strain relief option yes
Surface Nickel-plated
Thread Pg 9
Thread length 6 mm
Thread type PG
Type of seal Sealing ring
Version for Straight
WAF 17
With locknut no

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / V-TEC PG9 MS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.