

INDUSTRIAL COMPONENT DATA

V-TEC VM LM32 MS 2086135 OBO BETTERMANN Cable gland with long connection thread, M32, Nickel-plated, Brass, ..

Brand: OBO BETTERMANN | Manufacturer Part Number: V-TEC VM LM32 MS



Manufacturer	OBO BETTERMANN
MPN / Reference	V-TEC VM LM32 MS
Catalog number	2086135
Category	Cable gland
Minimum order	10 Pcs
Document ID	EO-58D95A64C9
Generated	2026-08-02

Product Overview

Cable gland with long connection thread, M32, Nickel-plated, Brass, CuZn

V-TEC VM LM32 MS cable gland, with long thread M32 Brass, CuZn, nickel-plated

Cap nut cable gland, metric thread, silver grey, long, nickel-plated. With metric connecting thread to IEC 423, robust cap nut cable gland with large sealing area. Strain relief, wringing protection and tightness over the whole clamping area. For thicker housing wall thicknesses in conjunction with locknuts. Neoprene sealing ring. Polyamide terminal insert. With pre-mounted sealing ring on connection thread, VDE-tested to DIN EN 50262, protection rating IP 68 at 5 bar for 1 hr. With long connection thread. * Prices according to DEL notation.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > metal GIs

Additional Product Information

Bend protection no

CO2 Footprint (GWP) Cradle-to-Gate 0,2 kg CO2e / 1 Piece

Dimension M32

Dimension E 36 mm

Dimension L max. 30 mm

Dimension L1 13 mm

Dimension L2 4,5 mm

Dimension L3 18,5 mm

explosion-proof no

Fibre-glass reinforced no
Flat cable gland no
For Ex zone Without
Halogen-free no
Impact-resistant no
Material Brass
Permitted temperature range, max. 100 °C
Permitted temperature range, min. -20 °C
Protection rating IP68
Sealing area D, max. 21 mm
Sealing area D, min. 14 mm
Sealing insert, multiple no
Strain relief option yes
Surface Nickel-plated
Thread M32 x 1,5
Thread length 13 mm
Thread type Metric
Type of seal Sealing ring
Version for Straight
WAF 34
With locknut no

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / V-TEC VM LM32 MS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.