

**INDUSTRIAL COMPONENT DATA**

# V-TEC VM20 MS 2086030 OBO BETTERMANN Cable gland , M20, Nickel-plated, Brass, CuZn

Brand: OBO BETTERMANN | Manufacturer Part Number: V-TEC VM20 MS



|                 |                |
|-----------------|----------------|
| Manufacturer    | OBO BETTERMANN |
| MPN / Reference | V-TEC VM20 MS  |
| Catalog number  | 2086030        |
| Category        | Cable gland    |
| Minimum order   | 25 Pcs         |
| Document ID     | EO-E0C46343AD  |
| Generated       | 2026-08-02     |

## Product Overview

Cable gland , M20, Nickel-plated, Brass, CuZn

Cap nut cable gland, metric thread, silver grey, nickel-plated. With metric connecting thread to IEC 423, robust cap nut cable gland with large sealing area. Strain relief, wringing protection and tightness over the whole clamping area. Neoprene sealing ring. Polyamide terminal insert. With pre-mounted O sealing ring on connection thread, VDE-tested to DIN EN 50262, protection rating IP68 at 5 bar for 1 hr, max. permitted ambient temperature -20 to +100°C.\* Prices according to DEL notation.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                                    |
|--------------|------------------------------------------------------------------------------------|
| Catalog path | OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > metal GIs |
|--------------|------------------------------------------------------------------------------------|

## Additional Product Information

Bend protection no

CO2 Footprint (GWP) Cradle-to-Gate 0,0806 kg CO2e / 1 Piece

Dimension M20

Dimension E 24 mm

Dimension L max. 27 mm

Dimension L1 6 mm

Dimension L2 3,5 mm

Dimension L3 16,5 mm

explosion-proof no

Fibre-glass reinforced no

Flat cable gland no  
For Ex zone Without  
Halogen-free no  
Hexagonal corner dimension 24 mm  
Impact-resistant no  
Material Brass  
Permitted temperature range, max. 100 °C  
Permitted temperature range, min. -20 °C  
Protection rating IP68  
Sealing area D, max. 13 mm  
Sealing area D, min. 9 mm  
Sealing insert, multiple no  
Strain relief option yes  
Surface Nickel-plated  
Thread M20 x 1,5  
Thread length 6 mm  
Thread type Metric  
Type of seal Sealing ring  
Unstable torque 3,5 Nm  
Version for Straight  
WAF 22  
With locknut no

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / V-TEC VM20 MS with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.