

INDUSTRIAL COMPONENT DATA

V-TEC VM40 EMV-K 2086181 OBO BETTERMANN Cable gland EMV contact spring-shielded cable, M40, Nickel-plated, B..

Brand: OBO BETTERMANN | Manufacturer Part Number: V-TEC VM40 EMV-K



Manufacturer	OBO BETTERMANN
MPN / Reference	V-TEC VM40 EMV-K
Catalog number	2086181
Category	Cable gland
Minimum order	5 Pcs
Document ID	EO-16DCAB65CF
Generated	2026-08-03

Product Overview

Cable gland EMV contact spring-shielded cable, M40, Nickel-plated, Brass, CuZn
 Cap nut cable gland, EMC spring contact, metric thread, nickel-plated. With metric connecting thread to IEC 423, robust EMV cap-nut cable gland with large sealing area. The contact between the gland and braided shield is made using a contact spring. Strain relief, wringing protection and tightness over the whole clamping area. Neoprene sealing ring. Polyamide terminal insert. With pre-mounted O sealing ring on connection thread, protection rating IP 68 at 5 bar for 1 hr.*
 Prices according to DEL notation.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > metal GIs**

Additional Product Information

Bend protection no
 CO2 Footprint (GWP) Cradle-to-Gate 0,4394 kg CO2e / 1 Piece
 Dimension M40
 Dimension D1 19 mm
 Dimension E 46 mm
 Dimension G M40x1,5 mm
 Dimension L 33 mm
 Dimension L1 8 mm
 Dimension L2 4,5 mm
 Dimension L3 16,4 mm

Fibre-glass reinforced no
Flat cable gland no
For Ex zone Without
Halogen-free no
Height 41 mm
Impact-resistant no
Length 43 mm
Material Brass
Permitted temperature range, max. 100 °C
Permitted temperature range, min. -20 °C
Protection rating IP68
Sealing area D, max. 27 mm
Sealing area D, min. 19 mm
Sealing insert, multiple no
Strain relief option yes
Surface Nickel-plated
Thread M40 x 1,5
Thread length 8 mm
Type of seal Sealing ring
Version for Straight
WAF 43
Width 46 mm
With locknut no

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / V-TEC VM40 EMV-K with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.