

**INDUSTRIAL COMPONENT DATA**

# S16W SW 2046565 OBO BETTERMANN Plug-in steel pipe , Ø16, 3000mm, Black, Painted, Steel, St

Brand: OBO BETTERMANN | Manufacturer Part Number: S16W SW



|                 |                         |
|-----------------|-------------------------|
| Manufacturer    | OBO BETTERMANN          |
| MPN / Reference | S16W SW                 |
| Catalog number  | 2046565                 |
| Category        | Metal installation tube |
| Minimum order   | 30 Pcs                  |
| Document ID     | EO-1DB8D8654A           |
| Generated       | 2026-07-31              |

## Product Overview

Plug-in steel pipe , Ø16, 3000mm, Black, Painted, Steel, St

Armoured steel pipe without thread, black. Electrical installation pipe without threaded ends according to EN 61386-1 for mechanical protection of cables. With burr-free inner wall.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                                     |
|--------------|-------------------------------------------------------------------------------------|
| Catalog path | OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > metal pipe |
|--------------|-------------------------------------------------------------------------------------|

## Additional Product Information

Brushed surface no  
 Cavity wall installation yes  
 Classification code 44561  
 CO2 Footprint (GWP) Cradle-to-Gate 0,769 kg CO2e / 1 Meter  
 Colour Jet black; RAL 9005  
 Concealed yes  
 Concrete installation yes  
 Connection 1, installation pipe Pipe end  
 Connection 2, installation pipe Pipe end  
 Dimension Ø16, 3000mm  
 Dimension D 16 mm  
 Dimension L 3000 mm  
 Dimension m (mm) M16

Dimension t 1 mm  
External diameter 16 mm  
Installation in the earth no  
Installation on wood yes  
Installation outdoors no  
Length 3000 mm  
Machines and system installation yes  
Material Steel  
Permitted temperature range, max. 250 °C  
Permitted temperature range, min. -45 °C  
Pipe version Rigid without thread  
Polished surface no  
Surface PES50 - Polyester/epoxy  
Surface-mounted yes  
Underfloor installation (bitumen, hot asphalt) yes  
Underfloor installation (screed) yes  
With sleeve no

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / S16W SW with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.