

## INDUSTRIAL COMPONENT DATA

**S40W FT 2046597 OBO BETTERMANN Plug-in steel pipe ,  
Ø40, 3000mm, Hot-dip galvanised, DIN EN ISO 1461, Steel,..**

Brand: OBO BETTERMANN | Manufacturer Part Number: S40W FT



|                 |                         |
|-----------------|-------------------------|
| Manufacturer    | OBO BETTERMANN          |
| MPN / Reference | S40W FT                 |
| Catalog number  | 2046597                 |
| Category        | Metal installation tube |
| Minimum order   | 15 m.                   |
| Document ID     | EO-A33AC3E6BF           |
| Generated       | 2026-08-01              |

**Product Overview**

Plug-in steel pipe , Ø40, 3000mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St  
Hot-dip galvanised steel pipe, without thread. Electrical installation pipe without threaded ends according to EN 61386-1 for mechanical protection of cables. With burr-free inner wall. Corrosion protection class 4 (high).

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > metal pipe

**Additional Product Information**

Brushed surface no  
Cavity wall installation yes  
Classification code 44571  
CO2 Footprint (GWP) Cradle-to-Gate 3,2045 kg CO2e / 1 Meter  
Concealed yes  
Concrete installation yes  
Connection 1, installation pipe Pipe end  
Connection 2, installation pipe Pipe end  
Dimension Ø40, 3000mm  
Dimension D 40 mm  
Dimension L 3000 mm  
Dimension m (mm) M40  
Dimension t 1,2 mm

External diameter 40 mm  
Installation in the earth yes  
Installation on wood yes  
Installation outdoors yes  
Length 3000 mm  
Machines and system installation yes  
Material Steel  
Permitted temperature range, max. 400 °C  
Permitted temperature range, min. -45 °C  
Pipe version Rigid without thread  
Polished surface no  
Surface Hot-dip galvanised  
Surface-mounted yes  
Underfloor installation (bitumen, hot asphalt) yes  
Underfloor installation (screed) yes  
With sleeve no

### REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / S40W FT with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

#### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.