

## INDUSTRIAL COMPONENT DATA

# SM25W FT 2046535 OBO BETTERMANN Threaded steel pipe with threaded sleeve, M25, 3000mm, Hot-dip galvanised, D..

Brand: OBO BETTERMANN | Manufacturer Part Number: SM25W FT



|                 |                         |
|-----------------|-------------------------|
| Manufacturer    | OBO BETTERMANN          |
| MPN / Reference | SM25W FT                |
| Catalog number  | 2046535                 |
| Category        | Metal installation tube |
| Minimum order   | 30 m.                   |
| Document ID     | EO-978E6D6C46           |
| Generated       | 2026-08-02              |

## Product Overview

Threaded steel pipe with threaded sleeve, M25, 3000mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St  
Hot-dip galvanised steel pipe, with thread. Electrical installation pipe according to EN 61386-1 with threaded ends to EN 60423 for mechanical protection of cables. With burr-free inner wall. Corrosion protection class 4 (high). One coupling is already screwed onto each pipe.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                                     |
|--------------|-------------------------------------------------------------------------------------|
| Catalog path | OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > metal pipe |
|--------------|-------------------------------------------------------------------------------------|

## Additional Product Information

Brushed surface no  
Cavity wall installation yes  
Classification code 55571  
CO2 Footprint (GWP) Cradle-to-Gate 2,0511 kg CO2e / 1 Meter  
Concealed yes  
Concrete installation yes  
Connection 1, installation pipe Sleeve  
Connection 2, installation pipe External thread (metric)  
Dimension M25, 3000mm  
Dimension D 25 mm  
Dimension I 18 mm  
Dimension L 3000 mm

Dimension m (mm) M25  
Dimension t 1,5 mm  
External diameter 25 mm  
Installation in the earth yes  
Installation on wood yes  
Installation outdoors yes  
Length 3000 mm  
Machines and system installation yes  
Material Steel  
Permitted temperature range, max. 400 °C  
Permitted temperature range, min. -45 °C  
Pipe version Rigid with thread  
Polished surface no  
Surface Hot-dip galvanised  
Surface-mounted yes  
Thread M25x1,5  
Underfloor installation (bitumen, hot asphalt) yes  
Underfloor installation (screed) yes  
With sleeve yes

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / SM25W FT with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.